

EUROLITE LED Outdoor Spot 15W RGBW QuickDMX with stake

Weather-proof LED spotlight (IP65) with 15 W LED, incl. IR remote control, frost filter & ground stake

Art. No.: 50498638

GTIN: 4026397696301



Features:

- Integrated QuickDMX transceiver for wireless DMX control
- Additional frost filter provides a wide, soft and homogeneous light
- 1 LED 15 W 4in1 RGBW (homogenous color mix)
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic; Dimmer speed (step response) adjustable; white balance
- Strobe effect
- 36 integrated show programs
- Direct color selection for 15 preset colors
- Can be operated in 3; 4; 6; 8; 11 CH mode
- The device is cooled by passive convection cooling
- Control via IR remote control; QuickDMX; master/slave function; stand-alone; sound to light via microphone; DMX
- Flicker-free
- Easy installation
- With a beam angle of 9°
- With mounting bracket
- LCD display
- Suitable for outdoor use IP65
- With pressure compensation membrane
- For application areas such as: Clubs/dancing school; decoration; mobile djs / entertainer; restaurants, bars and hotels; party room
- Silent operation
- Application possibility: Suspended; standing; on stand
- 3 buttons on the remote control for saving your own settings

Logistic

EAN / GTIN: 4026397696301

Weight: 1,80 kg

Length: 0.26 m

Width: 0.23 m

Height: 0.15 m

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	16 W
IP classification:	IP65
Protection class:	Protection class I
Power connection:	Fixed power supply cord with safety plug
Cable length:	Approx. 1 m
Lamp type:	LED lamp
LED type:	1 x 15 W 4in1 RGBW (homogenous color mix)
Flash rate:	1 - 23 Hz
DMX channels:	3; 4; 6; 8; 11
Cooling:	Passive convection cooling
Control:	IR remote control; QuickDMX; master/slave function; stand-alone; sound to light via microphone; DMX
Fixtures available for:	Light Captain; Light J
Projection:	Flicker-free
Carrier frequency:	2.4 GHz
Setup:	Easy installation
Beam angle:	9°
Beam angle (1/2 peak):	9°
Beam angle (1/10 peak):	22°
Housing color:	Black
Attachment system:	Mounting bracket
Display type:	LCD display
Material:	Aluminum casting
Dimensions:	Length: 14.3 cm Width: 11.0 cm Depth: 18.4 cm
Weight:	1.52 kg
Noise classification:	Class 0 (no noise at all)
Diameter mounting holes:	3 x Ø11mm; 2 x Ø6.5mm
Material:	Aluminum, 2 mm
Battery:	1 x button cell 3.0 V CR2032 lithium manganese built-in

Scope of delivery:

1 x light effect
1 x stake
1 x remote control
1 x frost filter
1 x screw
2 x washer
1 x declaration of conformity
1 x user manual