

## EUROLITE LED BREAKDANCE Beam Effect

Spectacular RGBW lighting effect with 3 rotating arms, atmospheric effect & unlimited PAN

Art. No.: 50944324

GTIN: 4026397759020



**List price: 474.81 €**

incl. 19% VAT.

### Features:

- 3 dynamically rotating arms with RGBW beam LEDs and atmospheric RGB lights
- Unlimited PAN rotation of the base and individual arms
- 12 LEDs 10 W SMD 5050 4in1 RGBW<BR> LEDs controlled separately
- 117 LEDs 0.2 W SMD 5050 3in1 RGB (homogenous color mix)
- Positioning within 540° PAN,
- Exact positioning (16 bit resolution)
- With a beam angle of 1° beam
- Control via stand-alone; sound to light; DMX; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional); master/slave function
- The device is cooled by cooling fan at the base
- Dimmer electronic; background color adjustable; Rotation direction adjustable; Rotation speed adjustable; color macros
- Flicker-free
- With omega bracket
- Mains input and output for power linking up to 8 units
- For application areas such as: Clubs/dancing school; installation; restaurants, bars and hotels
- Application possibility: Suspended
- Can be operated in 32; 73 CH mode

### Logistic

EAN / GTIN: 4026397759020

Weight: 11,75 kg

Length: 0.58 m

Width: 0.57 m

Height: 0.31 m

### Technical specifications:

Power supply: 100-240 V AC, 50/60 Hz

Power consumption: 150 W

Protection class: Protection class I

|                          |                                                                                                                                                                            |
|--------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Power connection:        | Mains input via P-Con (blue), mounting version power supply cord with safety plug                                                                                          |
| Cable construction:      | 3 x 1.0 mm <sup>2</sup> H05VV-F                                                                                                                                            |
| Power output:            | P-Con (grey), mounting version                                                                                                                                             |
| Fuse:                    | 5 x 20 mm, T 2 A fuse replaceable                                                                                                                                          |
| Lamp type:               | LED lamp                                                                                                                                                                   |
| LED type:                | 12 x 10 W SMD 5050 4in1 RGBW<br>117 x 0.2 W SMD 5050 3in1 RGB (homogenous color mix)                                                                                       |
| Max. PAN movement:       | 540° exact positioning (16 bit resolution) plus infinity                                                                                                                   |
| Flash rate:              | 2 - 25 Hz                                                                                                                                                                  |
| DMX channels:            | 32; 73                                                                                                                                                                     |
| DMX input:               | 3-pin XLR (M) mounting version                                                                                                                                             |
| DMX output:              | 3-pin XLR (F) mounting version                                                                                                                                             |
| Cooling:                 | 1 x cooling fan at the base                                                                                                                                                |
| Control:                 | Stand-alone; sound to light; DMX; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional); master/slave function |
| Fixtures available for:  | GDTF (GrandMA3)                                                                                                                                                            |
| Projection:              | Flicker-free                                                                                                                                                               |
| PWM frequency:           | 3000 Hz                                                                                                                                                                    |
| DMX fail mode:           | Zero values; hold                                                                                                                                                          |
| Beam angle:              | 1° beam                                                                                                                                                                    |
| Beam angle (1/2 peak):   | Beam 1° monochrome                                                                                                                                                         |
| Beam angle (1/10 peak):  | Beam 2°                                                                                                                                                                    |
| Lamp life:               | 20000 h                                                                                                                                                                    |
| Housing color:           | Black                                                                                                                                                                      |
| Attachment system:       | 2x omega bracket                                                                                                                                                           |
| Display type:            | Multicolor LCD display                                                                                                                                                     |
| Control elements:        | Power switch                                                                                                                                                               |
| Status LED:              | DMX, fault                                                                                                                                                                 |
| USB port:                | Type A                                                                                                                                                                     |
| Carrying handle:         | 2 pc/pcs                                                                                                                                                                   |
| Transport aid:           | 4 x rubber feet                                                                                                                                                            |
| Diameter mounting holes: | 2 x Ø11mm                                                                                                                                                                  |
| Material:                | Metal                                                                                                                                                                      |
| Dimensions:              | Width: 49.67 cm<br>Depth: 49.67 cm<br>Height: 25.4 cm                                                                                                                      |
| Weight:                  | 9.90 kg                                                                                                                                                                    |
| Noise classification:    | Class 3 (clearly perceptible sounds)                                                                                                                                       |

## Scope of delivery:

1 x moving light  
1 x power cord  
2 x omega bracket

1 x user manual