

EUROLITE LED BREAKDANCE Beam Effect

Spectacular RGBW lighting effect with 3 rotating arms, atmospheric effect & unlimited PAN

Art. No.: 50944324

GTIN: 4026397759020



Features:

- 3 dynamically rotating arms with RGBW beam LEDs and atmospheric RGB lights
- Unlimited PAN rotation of the base and individual arms
- 12 LEDs 10 W SMD 5050 4in1 RGBW
 LEDs controlled separately
- 117 LEDs 0.2 W SMD 5050 3in1 RGB (homogenous color mix)
- Positioning within 540° PAN,
- Exact positioning (16 bit resolution)
- With a beam angle of 1° beam
- Control via stand-alone; sound to light; DMX; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional); master/slave function
- The device is cooled by cooling fan at the base
- Dimmer electronic; background color adjustable; Rotation direction adjustable; Rotation speed adjustable; color macros
- Flicker-free
- With omega bracket
- Mains input and output for power linking up to 8 units
- For application areas such as: Clubs/dancing school; installation; restaurants, bars and hotels
- Application possibility: Suspended
- Can be operated in 32; 73 CH mode

Logistic

EAN / GTIN: 4026397759020

Weight: 11,75 kg

Length: 0.58 m

Width: 0.57 m

Height: 0.31 m

Technical specifications:

Power supply: 100-240 V AC, 50/60 Hz

Power consumption: 150 W

Protection class: Protection class I

Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug
Cable construction:	3 x 1.0 mm ² H05VV-F
Power output:	P-Con (grey), mounting version
Fuse:	5 x 20 mm, T 2 A fuse replaceable
Lamp type:	LED lamp
LED type:	12 x 10 W SMD 5050 4in1 RGBW 117 x 0.2 W SMD 5050 3in1 RGB (homogenous color mix)
Max. PAN movement:	540° exact positioning (16 bit resolution) plus infinity
Flash rate:	2 - 25 Hz
DMX channels:	32; 73
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	1 x cooling fan at the base
Control:	Stand-alone; sound to light; DMX; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional); master/slave function
Fixtures available for:	GDTF (GrandMA3)
Projection:	Flicker-free
PWM frequency:	3000 Hz
DMX fail mode:	Zero values; hold
Beam angle:	1° beam
Beam angle (1/2 peak):	Beam 1° monochrome
Beam angle (1/10 peak):	Beam 2°
Lamp life:	20000 h
Housing color:	Black
Attachment system:	2x omega bracket
Display type:	Multicolor LCD display
Control elements:	Power switch
Status LED:	DMX, fault
USB port:	Type A
Carrying handle:	2 pc/pcs
Transport aid:	4 x rubber feet
Diameter mounting holes:	2 x Ø11mm
Material:	Metal
Dimensions:	Width: 49.67 cm Depth: 49.67 cm Height: 25.4 cm
Weight:	9.90 kg
Noise classification:	Class 3 (clearly perceptible sounds)

Scope of delivery:

1 x moving light
1 x power cord
2 x omega bracket

1 x user manual