

ANTARI DarkFX Wash 2000

PRO DMX UV spot with 27 x 1.9 W UV LED, deep wavelength (365 nm)

Art. No.: 51100820

GTIN: 4719850658021



Description:

The Antari DarkFX Wash 2000 is an efficient high-output and low-power consumption UV LED wash panel that delivers a peak wavelength of 365 nm and radiant flux output of 20,290 mW at full intensity with minimum visible light. This ensures all UV-reactive materials reflect perfectly with stunningly bright and vivid colors.

Equipped with 27 x 1.9 W high-power UV LEDs arranged into 3 modular arrays, it features a 25° narrow beam angle, flicker-free operation, and special optics to prevent wear degradation from high UV exposure. This IP20-rated LED panel has been designed for indoor use only and comes with an aluminium housing with an adjustable bracket for versatile mounting options. The DarkFX Wash 2000 is operated in one of two modes: Either in DMX mode with 2 channels via the 5-pin XLR connectors or in stand-alone mode via the LCD display and the 4 operating buttons. Use the powerCON input to connect it to the mains.

Logistic

EAN / GTIN: 4719850658021

Weight: 7,30 kg

Length: 0.70 m

Width: 0.27 m

Height: 0.21 m

Features:

- Minimum visible light
- High output at full intensity
- Special optics will not degrade due to high UV exposure
- 27 LEDs 1.9 W high-power ultra violet (UV)
- UV effect
- Can be operated in 1; 2 CH mode
- Control via stand-alone; DMX
- Flicker-free
- With a beam angle of 25°
- With mounting bracket
- Built with NEUTRIK connector
- For further information about this product, please refer to the Data Sheet under "Downloads"

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	55 W
Power connection:	Mains input via PowerCON (blue), mounting version power supply cord with safety plug (provided)
Power output:	1 x PowerCON (grey)
Lamp type:	LED lamp
LED type:	27 x 1.9 W high-power ultra violet (UV)
DMX channels:	1; 2
DMX input:	1 x 5-pin XLR (M) mounting version
DMX output:	1 x 5-pin XLR (F) mounting version
Control:	Stand-alone; DMX
Projection:	Flicker-free
Beam angle:	25°
Beam angle (1/2 peak):	25°
Wavelength:	365 nm
Housing color:	Black
Attachment system:	Mounting bracket
Use of brands:	Built with NEUTRIK connector
Material:	Metal
Dimensions:	Width: 60 cm Depth: 17.4 cm Height: 17.9 cm
Weight:	6.35 kg

Scope of delivery:

1 x device
1 x user manual
1 x power cord