

ANTARI DarkFX IP Wash 2000

Weather-proof PRO DMX UV washlight with 33 x 1.9 W UV LED, deep wavelength (365 nm)

Art. No.: 51100826

GTIN: 4719850658212



The article is no longer in our assortment.

Description:

The Antari DarkFX IP Wash 2000 is an efficient high-output and low-power consumption UV LED wash panel that delivers a peak wavelength of 365 nm and radiant flux output of 24,800 mW at full intensity with minimum visible light. This ensures all UV-reactive materials reflect perfectly with stunningly bright and vivid colors. Equipped with 33 x 1.9 W high-power UV LEDs, it features a 25° narrow beam angle, flicker-free operation, and special optics to prevent wear degradation from high UV exposure. This IP65-rated LED panel is suitable for outdoor use and comes with an aluminium housing with an adjustable bracket for versatile mounting options.

The DarkFX IP Wash 2000 is operated in one of two modes: Either in DMX mode with 2 channels via the 3-pin XLR connectors or in stand-alone mode via the LCD display and the 4 operating buttons. Use the powerCON TRUE1 input to connect it to the mains.

Logistic

EAN / GTIN: 4719850658212

Weight: 11,60 kg

Length: 0.61 m

Width: 0.48 m

Height: 0.22 m

Features:

- Minimum visible light
- High output at full intensity
- Special optics will not degrade due to high UV exposure
- 33 LEDs 1.9 W high-power ultra violet (UV)
- UV effect
- Can be operated in 2; 1 CH mode
- Control via stand-alone
- With a beam angle of 25°
- With mounting bracket
- Built with NEUTRIK connector
- Suitable for outdoor use

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	70 W
IP classification:	IP65
Power connection:	Mains input via PowerCON TRUE (M) mounting version power supply cord with safety plug (provided)
Lamp type:	LED lamp
LED type:	33 x 1.9 W high-power ultra violet (UV)
DMX channels:	2; 1
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Control:	Stand-alone
Beam angle:	25°
Beam angle (1/2 peak):	25°
Wavelength:	368 nm
Housing color:	Black
Attachment system:	Mounting bracket
Use of brands:	Built with NEUTRIK connector
Dimensions:	Width: 11.6 cm Depth: 45.4 cm Height: 33.1 cm
Weight:	10.30 kg

Scope of delivery:

- 1 x device
- 1 x user manual
- 1 x power cord