

## ANTARI M-9 RGBAW Stage Fogger

1820 W fog machine with LED illumination, vertical & horizontal operation

Art. No.: 51701909

GTIN: 4719850654887



### Features:

- Output nozzle with RGBAW LED illumination for impressive effect presentations
- New housing design allows upward and downward fog output
- Adjustable timer with interval, duration and output volume
- Continuous output
- Rugged metal housing
- 27 LEDs 8 W SMD 9080 5in1 RGBWA (homogenous color mix)
- Output distance: Vertical approx. 10 m
- Output distance: Horizontal approx. 12 m
- Big tank capacity
- With level indication
- Operates on water-based fluid
- Removable tank
- 8 integrated show programs
- Direct color selection for 25 preset colors
- Can be operated in 10; 15; 25 CH mode
- Control via wireless remote control; W-DMX by wireless solution (optional); DMX; master/slave function; timer
- Wireless remote control: operating range up to 50m
- Built with NEUTRIK connector
- For application areas such as: Clubs/dancing school; stage; theater; rental
- Application possibility: Standing

### Logistic

EAN / GTIN: 4719850654887

Weight: 27,00 kg

Length: 0.55 m

Width: 0.47 m

Height: 0.57 m

## Technical specifications:

|                       |                                                                                                   |
|-----------------------|---------------------------------------------------------------------------------------------------|
| Power supply:         | 230 V AC, 50 Hz                                                                                   |
| Power consumption:    | 1670 W                                                                                            |
| Power connection:     | Mains input via PowerCON TRUE (M) mounting version power supply cord with safety plug (provided)  |
| Lamp type:            | LED lamp                                                                                          |
| LED type:             | 27 x 8 W SMD 9080 5in1 RGBWA (homogenous color mix)                                               |
| Warm-up time:         | Approx. 14 min                                                                                    |
| Output distance:      | Vertical approx. 10 m<br>Horizontal approx. 12 m                                                  |
| Tank capacity:        | 6 l water-based fluid removable tank                                                              |
| Fluid consumption:    | Approx. 400 ml/min                                                                                |
| DMX channels:         | 10; 15; 25                                                                                        |
| DMX input:            | 3-pin XLR (M) mounting version<br>5-pin XLR (M) mounting version                                  |
| DMX output:           | 3-pin XLR (F) mounting version<br>5-pin XLR (F) mounting version                                  |
| Control:              | Wireless remote control; W-DMX by wireless solution (optional); DMX; master/slave function; timer |
| Range:                | Wireless remote control: range up to 50m                                                          |
| Carrier frequency:    | 433.92 MHz                                                                                        |
| Housing color:        | Black                                                                                             |
| Use of brands:        | Built with NEUTRIK connector                                                                      |
| Color:                | Black                                                                                             |
| Dimensions:           | Width: 32.1 cm<br>Depth: 39.3 cm<br>Height: 42 cm                                                 |
| Weight:               | 24.85 kg                                                                                          |
| Noise classification: | Class 3 (clearly perceptible sounds)                                                              |

## Scope of delivery:

1 x device  
1 x user manual  
1 x power cord  
1 x remote control  
1 x declaration of conformity  
1 x container  
2 x tube  
1 x battery