LASERWORLD CS-12.000RGB FX MK2

Pure diode laser system

Art. No.: 51743238

GTIN: 7640144996031









The article is no longer in our assortment.

Features:

- The device is cooled by cooling fan
- Control via DMX; stand-alone; sound to light via microphone; ILDA; master/slave function
- 4 digit 7-segment LED display
- For application areas such as: Clubs/dancing school
- Application possibility: Suspended

Logistic

EAN / GTIN: 7640144996031
Weight: 8,90 kg
Length: 0.45 m
Width: 0.32 m
Heigth: 0.26 m

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	200 W
IP classification:	IP4X
Protection class:	Protection class I
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug
Power output:	1 x P-Con (grey), mounting version
Laser class:	4
Laser color:	R/G/B
Laser module:	Red (R) 2600 mW 638nm Green (G) 2900 mW 520nm Blue (B) 5500 mW 450nm

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Cooling:	Cooling fan
Control:	DMX; stand-alone; sound to light via microphone; ILDA; master/slave function
Housing color:	Black
Display type:	4 digit 7-segment LED display
Dimensions:	Length: 28.5 cm Width: 18 cm Height: 19 cm
Weight:	7.80 kg

Scope of delivery:

1 x laser
1 x user manual
1 x power cord
1 x Interlock
1 x key

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.