

LASERWORLD DS-1000RGB MK4

Diode showlaser with ShowNET network interface and free software

Art. No.: 51743288

GTIN: 7640144997533



The article is no longer in our assortment.

Features:

- Integrated show programs
- The device is cooled by passive convection cooling
- Control via stand-alone; DMX; ILDA; Art-Net; master/slave function
- For application areas such as: Clubs/dancing school; stage; wedding/gala/events; rental
- Application possibility: Suspended

Logistic

EAN / GTIN: 7640144997533

Weight: 4,75 kg

Length: 0.35 m

Width: 0.30 m

Height: 0.19 m

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	40 W
IP classification:	IP4X
Protection class:	Protection class I
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Power output:	1 x P-Con (grey), mounting version
Laser class:	4
Laser color:	R/G/B
Laser module:	Red (R) 200 mW 638nm Green (G) 250 mW 520nm Blue (B) 700 mW 450nm

DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Passive convection cooling
Control:	Stand-alone; DMX; ILDA; Art-Net; master/slave function
Housing color:	Black
Dimensions:	Width: 14 cm Depth: 20 cm Height: 11 cm
Weight:	4.00 kg

Scope of delivery:

- 1 x laser
- 1 x user manual
- 1 x power cord
- 2 x key
- 1 x Interlock