

LASERWORLD DS-15.000RGB IP65

Diode showlaser with ShowNET network interface and free software

Art. No.: 51743296

GTIN: 7640144996086



Features:

- Full color mixing laser with analog color modulation
- Control via stand-alone; Art-Net; DMX; ILDA
- Integrated show programs
- With mounting bracket
- Suitable for outdoor use IP65
- The device is cooled by temperature-controlled fan

Logistic

EAN / GTIN: 7640144996086

Weight: 13,20 kg

Length: 0.46 m

Width: 0.36 m

Height: 0.28 m

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	120 W
IP classification:	IP65
Protection class:	Protection class I
Power connection:	Mains input via IP T-Con (M) mounting version power supply cord with safety plug
Power output:	1 x IP T-Con (F) mounting version
Laser class:	4
Laser color:	R/G/B
Laser module:	Blue (B) 8000 mW 450nm Green (G) 4500 mW 520nm

	Red (R) 4000 mW 638nm
DMX input:	1 x 3-pin XLR (F) mounting version IP
DMX output:	1 x 3-pin XLR (M) mounting version IP
Cooling:	Temperature-controlled fan
Control:	Stand-alone; Art-Net; DMX; ILDA
Housing color:	Black
Attachment system:	Mounting bracket
Dimensions:	Length: 29.2 cm
	Width: 23.2 cm
	Height: 20.1 cm
Weight:	11.90 kg

Scope of delivery:

- 1 x laser
- 1 x user manual
- 1 x power cord
- 2 x key
- 1 x Interlock
- 1 x bag
- 1 x cable