


LASERWORLD tarm BLAZE Moving Head

Weather-proof moving head with white light laser

Art. No.: 51743310

GTIN: 7640144990886



The article is no longer in our assortment.

Features:

- Positioning within 540° PAN, 270° TILT
- Exact positioning (16 bit resolution)
- Prism 6-fold linear rotating; prism 16-fold rotating; frost filter rotating; color wheel; gobo wheel with rotating gobos; gobo wheel with static gobos; focus motor-driven
- Pulse-width modulation; Dimmer electronic
- Beam effect; spot effect
- CMY color mixing for indefinite color variations
- Color wheel with 19 dichroic filters plus open and CTO correction filter
rainbow effect with adjustable speed in both directions
- Gobo wheel with static gobos, 19 gobos and open
shake effect
- Gobo wheel with rotating gobos, 6 glass gobos an open
shake effect
- Laser class 1
 does not require additional protective measures or appointment of a laser safety officer
- Can be operated in 19; 23; 27 CH mode
- Control via CRMX by LumenRadio; sACN; RDM; Art-Net; DMX
- Suitable for outdoor use IP66

Logistic

EAN / GTIN: 7640144990886

Weight: 48,00 kg

Length: 0.84 m

Width: 0.52 m

Height: 0.48 m

Bulky product

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	240 W
IP classification:	IP66
Protection class:	Protection class I

Power connection:	Mains input via IP T-Con (M) mounting version power supply cord with safety plug
Power output:	1 x IP T-Con (F) mounting version
Max. TILT movement:	270° exact positioning (16 bit resolution)
Max. PAN movement:	540° exact positioning (16 bit resolution)
Equipment:	Prism 6-fold linear rotating; prism 16-fold rotating; frost filter rotating; color wheel; gobo wheel with rotating gobos; gobo wheel with static gobos; focus motor-driven
Color generation:	CMY color mixing for indefinite color variations
Color generation:	Color wheel with 19 dichroic filters plus open and CTO correction filter Rainbow effect with adjustable speed in both directions
Gobos:	Gobo wheel with static gobos, 19 gobos and open Shake effect Gobo wheel with rotating gobos, 6 glass gobos an open Shake effect
Laser class:	1
DMX channels:	19; 23; 27
DMX input:	1 x 5-pin XLR (M) mounting version IP
DMX output:	1 x 3-pin XLR (F) mounting version IP
Control:	CRMX by LumenRadio; sACN; RDM; Art-Net; DMX
DMX fail mode:	Hold; blackout
Housing color:	Black
USB port:	1 x type C
Dimensions:	Length: 38.1 cm Width: 28.0 cm Height: 66.5 cm
Weight:	24.00 kg

Scope of delivery:

1 x device
1 x user manual
1 x power cord
2 x omega bracket