

EUROLITE LED TMH-61 Hypno Moving Head Beam

Beam with 4 hypno rings and 60 W LED in RGBW colors

Art. No.: 51785896

GTIN: 4026397592924



The article is no longer in our assortment.

Features:

- Beam effect with a 60 W COB LED in RGBW colors and 4 hypno rings with altogether 88 RGB SMD LEDs
- Compact lightweight
- 12, 27 or 29 DMX channels selectable
- Stepless RGBW color mixture, color presets and color change
- Masterdimmer
- Strobe effect with 1-25 flashes per second and with adjustable speed
- Random strobe effect
- Internal programs
- LED hypno rings with stepless RGB color mixture - each color and each ring can be controlled individually, color presets and color changes
- Automatic position correction
- Positioning within 630° PAN and 210° TILT
- PAN-angle switchable between 630° and 540°
- Exact positioning via 16 bit PAN/TILT movement resolution
- DMX-controlled operation or stand-alone operation with Master/Slave function
- Sound-controlled via built-in microphone, sensitivity adjustable
- Addressing via control panel with 4-digit LED display
- Switch-mode power supply for operation between 100 and 240 volts
- Ready for connection with power cord and safety plug
- DMX512 control via every standard DMX controller
- Beam effect
- The device is cooled by cooling fan
- Control via stand-alone; DMX
- Flicker-free
- With a beam angle of 2.5°

Logistic

EAN / GTIN: 4026397592924

Weight: 6,25 kg

Length: 0.44 m

Width: 0.28 m

Height: 0.35 m

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	80 W
Lamp type:	LED lamp
Cooling:	Cooling fan
Control:	Stand-alone; DMX
Fixtures available for:	Light J; LED PC-Control 512; Light Captain
Projection:	Flicker-free
Beam angle:	2.5°
Beam angle (1/2 peak):	2.5°
Housing color:	Black
Dimensions:	Width: 24.5 cm Depth: 16.5 cm Height: 35 cm
Weight:	5.40 kg
DMX channels:	12/27/29
DMX connection:	3-pin XLR
Sound-control:	via built-in microphone
Flash-rate:	25 Hz
LED number:	1 x COB + 88 x SMD
LED type:	60 W COB, RGBW + RGB SMD
Maximum PAN-movement:	630°
Maximum TILT-movement:	210°
Dimensions (L x W x H):	165 x 245 x 350 mm

Scope of delivery: