

EUROLITE LED TMH-X19 Moving-Head Wash Zoom

Washlight with 19 x 25 W LEDs, 7in1 RGBWAL/UV color mixing and motorized zoom

Art. No.: 51785903

GTIN: 4026397616316



Features:

- Moving Head Washlight with nineteen 7in1 LEDs and zoom
- Equipped with nineteen 25 W LEDs in the colors red, green, blue, amber, white, lemon and UV
- 22 or 36 DMX channels selectable
- Different LED segments, which can be controlled individually via DMX
- Positioning within 540° PAN and 270° TILT
- Stepless RGBAWL+UV color mixture
- Color presets
- 12 Macros
- 5 internal color-programs
- Dimmer
- Dimmer speed (step response) adjustable
- Motorized zoom with 4-58° beam angle
- Sound-control via built-in microphone; sensitivity adjustable
- Strobe effect with adjustable speed, random strobe effect
- Automatic position correction
- Exact positioning via 16 bit PAN/TILT movement resolution
- PAN angle switchable between 540° and 360°
- DMX-controlled operation or stand-alone operation with Master/Slave function
- Control board with color LCD for adjusting the DMX-starting address, PAN/TILT Reverse, Reset
- Switch-mode power supply for operation between 100 and 240 volts
- P-Con terminals for power linking up to 8 units
- 19 LEDs 25 W high-power 7in1 RGBWAL/UV (homogenous color mix)
- PAN angle switchable between 540° and 360°
- Auto position correction (feedback)
- Exact positioning (16 bit resolution)
- Zoom motor driven

Logistic

EAN / GTIN: 4026397616316

Weight: 16,25 kg

Length: 0.45 m

Width: 0.36 m

Height: 0.54 m

- Strobe effect
- Can be operated in 22; 36 CH mode
- The device is cooled by cooling fan
- Control via stand-alone; sound to light via microphone
- Flicker-free
- With a beam angle of 4° - 58°

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	350 W
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Power output:	1 x P-Con (grey), mounting version
Lamp type:	LED lamp
LED type:	19 x 25 W high-power 7in1 RGBWAL/UV (homogenous color mix)
Max. TILT movement:	270° exact positioning (16 bit resolution) auto position correction (feedback)
Max. PAN movement:	540°, 360° exact positioning (16 bit resolution) auto position correction (feedback)
Flash rate:	0 - 20 Hz
Equipment:	Zoom motor driven
DMX channels:	22; 36
DMX input:	1 x 3-pin XLR (M) mounting version 1 x 5-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version 1 x 5-pin XLR (F) mounting version
Cooling:	Cooling fan
Control:	Stand-alone; sound to light via microphone
Fixtures available for:	Light´J; LED PC-Control 512; Light Captain
Projection:	Flicker-free
Beam angle:	4° - 58°
Beam angle (1/2 peak):	4 - 31°
Beam angle (1/10 peak):	9 - 58°
Housing color:	Black
Dimensions:	Width: 38 cm Depth: 23.1 cm Height: 49.8 cm
Weight:	14.40 kg

Scope of delivery:

- 1 x device
- 1 x user manual
- 1 x power cord
- 2 x omega bracket
- 1 x XLR cable