

EUROLITE LED TMH-X25 Zoom Moving-Head

5x5 Matrix Panel, bright 12 W RGBW LEDs, large zoom

Art. No.: 51785910

GTIN: 4026397597998



The article is no longer in our assortment.

Features:

- Quick and easy control via Art-Net
- Infinity function for unlimited PAN and TILT movement
- Individual control of each LED
- Stepless color blend, color change, preset colors, figure and letter patterns, dimmer and strobe effect
- Various dimmer curves with adjustable response
- Automatic position correction
- Exact positioning via 16 bit PAN/TILT movement resolution
- PAN angle switchable between 540° and 630°
- Ethernet connectors
- Mains input and output for power linking up to 8 units
- 25 LEDs 12 W COB (chip-on-board) 4in1 RGBW (homogenous color mix)
- PAN angle switchable between 540° and 630°
- Auto position correction (feedback)
- Exact positioning (16 bit resolution)
- Zoom motor driven
- Beam effect
- Can be operated in 13; 24; 88; 113 CH mode
- The device is cooled by cooling fan
- Control via DMX; stand-alone
- Flicker-free
- With a beam angle of 7.5° - 69°

Logistic

EAN / GTIN: 4026397597998

Weight: 23,00 kg

Length: 0.64 m

Width: 0.41 m

Height: 0.51 m

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	450 W
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Lamp type:	LED lamp
LED type:	25 x 12 W COB (chip-on-board) 4in1 RGBW (homogenous color mix)
Max. TILT movement:	Exact positioning (16 bit resolution) plus infinity auto position correction (feedback)
Max. PAN movement:	540°, 630° exact positioning (16 bit resolution) plus infinity auto position correction (feedback)
Flash rate:	0 - 20 Hz
Equipment:	Zoom motor driven
DMX channels:	13; 24; 88; 113
DMX input:	1 x 3-pin XLR (M) mounting version 1 x 5-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version 1 x 5-pin XLR (F) mounting version
Network connection:	Protocol: Art-Net 3 via 2x RJ-45 E-Con (F) mounting version
Cooling:	Cooling fan
Control:	DMX; stand-alone
Fixtures available for:	LED PC-Control 512; Light Captain; Light´J
Projection:	Flicker-free
Beam angle:	7.5° - 69°
Beam angle (1/2 peak):	7.5 - 60°
Beam angle (1/10 peak):	11 - 69°
Illuminance in Lux (lx):	Narrow red (R) 3m: 4095 lx, 6m: 1114 lx Wide red (R) 3m: 238 lx, 6m: 66 lx Narrow green (G) 3m: 8135 lx, 6m: 2314 lx Wide green (G) 3m: 493 lx, 6m: 140 lx Narrow blue (B) 3m: 1638 lx, 6m: 476 lx Wide blue (B) 3m: 102 lx, 6m: 30 lx Narrow cold white (CW) 3m: 10691 lx, 6m: 3011 lx Wide cold white (CW) 3m: 626 lx, 6m: 179 lx Narrow all 3m: 22665 lx, 6m: 6337 lx Wide all 3m: 1345 lx, 6m: 380 lx
Housing color:	Black
Dimensions:	Width: 41.5 cm Depth: 31 cm Height: 53.5 cm
Weight:	18.40 kg
Noise classification:	Class 3 (clearly perceptible sounds)

Scope of delivery:

1 x moving light
1 x user manual
1 x power cord
1 x XLR cable
1 x network cable
2 x omega bracket