

EUROLITE LED TMH FE-1800 Beam/Flower Effect

RGBW moving head flower with large zoom range and 18 x 12 W LED

Art. No.: 51785957

GTIN: 4026397554441



Features:

- Equipped with 18 x 12 W COB LED with RGBW colors, distributed in 6 segments
- Each segment can be controlled individually via DMX
- 20 or 40 DMX channels selectable
- Functions: colored beams in R, G, B and W, preset colors, built-in program, strobe effect with variable speed, dimmer, sound-control, Master/Slave operation
- Adjustable zoom movement - from narrow single beam to room-filling beams - via rotating lens
- Different patterns and movements can be selected via DMX
- Stepless RGBW color mixture
- Positioning within 540° PAN and 190° TILT
- PAN-angle switchable between 540° and 360°
- Dimmer speed (step response) adjustable
- Automatic position correction
- Exact positioning via 16 bit PAN/TILT movement resolution
- DMX-controlled operation or stand-alone operation with Master/Slave function
- Sound-controlled via built-in microphone
- Control board with LC display for adjusting the DMX-starting address, PAN/TILT reverse, reset
- Neutrik powerCON terminals for power linking up to 8 units
- Switch-mode power supply for operation between 100 and 240 volts
- 18 LEDs 12 W COB (chip-on-board) 4in1 RGBW
- PAN angle switchable between 540° and 360°
- Auto position correction (feedback)
- Exact positioning (16 bit resolution)
- Multi beam effect; beam effect
- Can be operated in 20; 40 CH mode
- The device is cooled by cooling fan
- Control via DMX; sound to light via microphone

Logistic

EAN / GTIN: 4026397554441

Weight: 11,75 kg

Length: 0.42 m

Width: 0.48 m

Height: 0.33 m

- Flicker-free
- With a beam angle of 6.5°

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	310 W
Power connection:	Mains input via PowerCON (blue), mounting version power supply cord with safety plug (provided)
Power output:	1 x PowerCON (grey)
Lamp type:	LED lamp
LED type:	18 x 12 W COB (chip-on-board) 4in1 RGBW
Max. TILT movement:	190° exact positioning (16 bit resolution) auto position correction (feedback)
Max. PAN movement:	540°, 360° exact positioning (16 bit resolution) auto position correction (feedback)
Flash rate:	0 - 18 Hz
DMX channels:	20; 40
DMX input:	1 x 3-pin XLR (M) mounting version 1 x 5-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version 1 x 5-pin XLR (F) mounting version
Cooling:	Cooling fan
Control:	DMX; sound to light via microphone
Fixtures available for:	Light´J; LED PC-Control 512; Light Captain
Projection:	Flicker-free
Beam angle:	6.5°
Beam angle (1/2 peak):	6.5°
Housing color:	Black
Dimensions:	Width: 33 cm Depth: 24 cm Height: 43 cm
Weight:	10.45 kg

Scope of delivery:

- 1 x moving light
- 1 x user manual
- 1 x power cord
- 1 x omega bracket
- 1 x XLR cable