EUROLITE LED TMH-30 MK2 Moving Head Spot COB

Versatile LED Head Spot with 30 W COB LED

Art. No.: 51785981

GTIN: 4026397541151











Features:

- Compact lightweight
- 14, 11 or 2 DMX channels selectable
- Equipped with a 30 W COB LED
- 7 brilliant, dichroic colors plus white
- Rainbow effect with adjustable speed in both directions
- Gobo-wheel 1 with 6 rotating gobos plus open
- With gobo-shake function
- Gobo-wheel 2 with 8 static metal gobos plus open
- 3-facet prism (rotating)
- Preprogrammed scenes in Program Run for stand-alone operation
- Electronic dimmer
- Motorized focus
- Programmable color-change speed and strobe effect
- Sound-controlled via built-in microphone
- Fan-cooled
- Exact positioning via 16 bit PAN/TILT movement resolution
- PAN-angle switchable between 540°, 360° and 180° (in sound and auto mode)
- TILT-angle switchable between 270°, 180° and 90° (in sound and auto mode)
- DMX-controlled operation or stand-alone operation with Master/Slave function
- Control board with LC display and foil-keyboard for adjusting the DMX-starting address, PAN/TILT Reverse, Program, Reset
- Switch-mode power supply for operation between 100 and 240 Volts
- DMX control via every standard DMX controller

Logistic

EAN / GTIN: 4026397541151
Weight: 9,40 kg
Length: 0.37 m
Width: 0.38 m
Heigth: 0.34 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Fixtures available for:	Light´J; LED PC-Control 512; EASY SHOW 1; Light Captain
Dimensions:	Width: 24.5 cm Depth: 25 cm Height: 31.5 cm
Power consumption:	95 W
DMX channels:	2/11/14
DMX connection:	3-pin XLR
Sound-control:	via built-in microphone
Color-wheel:	7 colors and open
Rotating gobo-wheel:	6 gobos and open
Static gobo-wheel:	8 gobos and open
LED number:	1
LED type:	30 W
Beam angle:	14°
Maximum PAN-movement:	540°
Maximum TILT-movement:	270°
Dimensions (L x W x H):	250 x 245 x 315 mm
Weight:	7.8 kg

Scope of delivery:

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.