

EUROLITE LED TMH-X20 Moving Head Spot

Bright spot with 200 W LED, zoom, gobo wheels, color wheel, 2 prisms

Art. No.: 51785987

GTIN: 4026397597943



Features:

- Equipped with a white 200 W COB LED
- Switchable color change (mode 1: only full colors, mode 2: color-change at every position)
- Rainbow effect with adjustable speed in both directions
- Effect wheel with rotating 6 fold linear prism and 3-facet prism
- The prism rotate in both directions and at different speeds
- Exact positioning via 16 bit PAN/TILT movement resolution
- Positioning within 540° PAN and 270° TILT
- Strobe effect with 1-18 flashes per second
- Strobe effect with adjustable speed
- Random strobe effect
- Motorized zoom (12°-23°)
- Motorized focus
- Iris
- Dimmer
- DMX-controlled operation or stand-alone operation with Master/Slave function
- Sound control; microphone sensitivity adjustable via control board
- Internal programs
- Automatic position correction
- Control board with touch LCD and foil-keyboard for adjusting the DMX-starting address, PAN/TILT Reverse, Program, Reset
- P-Con terminals for power linking up to 8 units
- Switch-mode power supply for operation between 100 and 240 volts
- 1 LED 200 W high-power cold white (CW)
- Auto position correction (feedback)
- Exact positioning (16 bit resolution)

Logistic

EAN / GTIN: 4026397597943

Weight: 20,75 kg

Length: 0.59 m

Width: 0.44 m

Height: 0.54 m

- Gobo wheel with rotating gobos; gobo wheel with static gobos; prism linear; prism 3-fold; focus motor-driven; iris; zoom motor driven
- Gobo effect; beam effect
- Color wheel with 7 dichroic filters plus open
- Gobo wheel with static gobos, 9 gobos and open
- Gobo wheel with rotating gobos, 7 gobos and open
gobos changeable
- Shake effect
- Slot-in gobo system for easy gobo replacement
- Can be operated in 18 CH mode
- The device is cooled by cooling fan
- Control via stand-alone; DMX; sound to light via microphone
- Flicker-free
- With a beam angle of 12° - 23°

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	260 W
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Power output:	1 x P-Con (grey), mounting version
Lamp type:	LED lamp
LED type:	1 x 200 W high-power cold white (CW)
Max. TILT movement:	270° exact positioning (16 bit resolution) auto position correction (feedback)
Max. PAN movement:	540° exact positioning (16 bit resolution) auto position correction (feedback)
Flash rate:	0 - 18 Hz
Equipment:	Gobo wheel with rotating gobos; gobo wheel with static gobos; prism linear; prism 3-fold; focus motor-driven; iris; zoom motor driven
Color generation:	Color wheel with 7 dichroic filters plus open
Gobos:	Gobo wheel with static gobos, 9 gobos and open Gobo wheel with rotating gobos, 7 gobos and open Outside diameter 25mm Image diameter 23mm Gobos changeable Shake effect Slot-in gobo system for easy gobo replacement
DMX channels:	18
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	Cooling fan
Control:	Stand-alone; DMX; sound to light via microphone
Fixtures available for:	LED PC-Control 512; Light Captain
Projection:	Flicker-free
Beam angle:	12° - 23°
Beam angle (1/2 peak):	12 - 23°
Beam angle (1/10 peak):	12 - 23°
Housing color:	Black
Dimensions:	Width: 42.5 cm

Depth: 33 cm
Height: 48.5 cm

Weight: 17.95 kg

Scope of delivery:

2 x omega bracket