

EUROLITE BE-200 Barrel Effect for 5R

Bright mirror barrel effect for OSD 5 Reflector 200W discharge lamp

Art. No.: 51786001

GTIN: 4026397535822



Features:

- 3 axes mirror deflection
- Strobe effect with adjustable speed (1-13 flashes/sec.)
- Mechanic dimmer
- DMX-controlled operation or stand-alone operation with Master/Slave function
- 7 internal programs can be called up via DMX-controller
- Microphone sensitivity adjustable via control board
- Control board with LC display and foil keyboard or adjusting the DMX-starting address, PAN/TILT reverse, program, reset, lamp on/off, operating hours
- For OMNILUX OSD 5 Reflector 200W or MSD Platinum 5R discharge lamp
- Switch-mode power supply for operation between 100 and 240 volts
- Power connection via Neutrik PowerCon jack and included power cable
- DMX-control via every standard DMX-controller
- Gobos
- Multi beam effect; mirror cylinder effect
- Color wheel with 13 dichroic filters plus open
rainbow effect with adjustable speed in both directions
- Gobo wheel with static gobos, 14 gobos und open
shake effect
- Can be operated in 8 CH mode
- The device is cooled by cooling fan
- Control via stand-alone; DMX; sound to light via microphone

Logistic

EAN / GTIN: 4026397535822

Weight: 8,20 kg

Length: 0.56 m

Width: 0.35 m

Height: 0.33 m

Technical specifications:

Power supply: 100-240 V AC, 50/60 Hz

Power consumption:	275 W
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Flash rate:	1 - 13 Hz
Equipment:	Gobos
Color generation:	Color wheel with 13 dichroic filters plus open Rainbow effect with adjustable speed in both directions
Gobos:	Gobo wheel with static gobos, 14 gobos und open Shake effect
DMX channels:	8
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Cooling fan
Control:	Stand-alone; DMX; sound to light via microphone
Housing color:	Black
Dimensions:	Width: 43 cm Depth: 23 cm Height: 32 cm
Weight:	6.75 kg

Scope of delivery: