

EUROLITE LED TMH Bar B240 Moving Head Beam

LED lighting system with 4 individually controllable 60 W moving heads

Art. No.: 51786059

GTIN: 4026397753660



List price: 950.81 €

incl. 19% VAT.

Description:

This moving head bar is equipped with four beam moving heads, each producing a very bright and narrow beam based on the colors red, green, blue, and white.

The bar can be used flexibly; mounted on a stand, placed on the floor, or suspended from a truss. Special attention has been given to ease of control, ensuring that even smaller DMX controllers can operate the bar without difficulty. Dedicated modes allow a variety of positions, movements, chases, and effects to be created using only a few DMX channels.

A great example of a suitable controller is the Eurolite Color Chief, which works perfectly with this bar.

Logistic

EAN / GTIN: 4026397753660

Weight: 14,00 kg

Length: 1.08 m

Width: 0.32 m

Height: 0.23 m

Features:

- 4 LEDs 60 W SMD 6065 4in1 RGBW
 moving lights effects controlled separately
- Positioning within 540° PAN, 180° TILT
- Exact positioning (16 bit resolution)
- Dimmer electronic; color selection; Motion macros adjustable; color macros adjustable
- Beam effect
- 22 integrated show programs
- Can be operated in 4; 8; 13; 15; 23; 27; 40; 48 CH mode
- The device is cooled by cooling fan at the base; cooling fan at the head
- Control via stand-alone; sound to light via microphone; DMX; master/slave function; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
- Flicker-free
- With a beam angle of 2°
- With omega bracket
- 4 digit 7-segment LED display

- 4 x rubber feet
- Mains input and output for power linking up to 8 units
- For application areas such as: Clubs/dancing school; wedding/gala/events; party room; mobile use; stage; mobile djs / entertainer; restaurants, bars and hotels
- Application possibility: Standing; suspended; on stand

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	230 W
Protection class:	Protection class I
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug
Cable construction:	3 x 1.0 mm ² H05VV-F
Power output:	P-Con (grey), mounting version
Fuse:	5 x 20 mm, T 2 A
Lamp type:	LED lamp
LED type:	4 x 60 W SMD 6065 4in1 RGBW
Max. TILT movement:	180° exact positioning (16 bit resolution)
Max. PAN movement:	540° exact positioning (16 bit resolution)
Flash rate:	2 - 15 Hz
DMX channels:	4; 8; 13; 15; 23; 27; 40; 48
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	2 x cooling fan at the base 4 x cooling fan at the head
Control:	Stand-alone; sound to light via microphone; DMX; master/slave function; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
Fixtures available for:	Light´J; Light Captain; Colorchief
Projection:	Flicker-free
PWM frequency:	11000 Hz
DMX fail mode:	Hold; blackout
Beam angle:	2°
Beam angle (1/2 peak):	2°
Beam angle (1/10 peak):	3°
Lamp life:	20000 h
Housing color:	Black
Attachment system:	Tube: Ø 35mm 2x omega bracket
Display type:	4 digit 7-segment LED display
Control elements:	Power switch
USB port:	Type A
Transport aid:	4 x rubber feet
Diameter mounting holes:	2 x Ø10mm
Material:	Steel

Dimensions:	Width: 100.0 cm
	Depth: 17.5 cm
	Height: 25.5 cm
Weight:	12.55 kg
Noise classification:	Class 2 (slight noise)

Scope of delivery:

- 1 x moving light
- 1 x user manual
- 1 x power cord
- 2 x omega bracket
- 2 x safety eyelet