

EUROLITE LED TMH-H60 Hybrid Moving Head Spot/Flower

Compact moving head spot with color wheel, static gobo wheel, flower effect and hypno ring

Art. No.: 51786071

GTIN: 4026397754957



List price: 355.81 €

incl. 19% VAT.

Description:

This moving head offers more than meets the eye. At its center is a 60 W LED, combined with a gobo wheel featuring seven gobos and a color wheel with eight colors. The spot has a beam angle of 14°, making it ideal for precise projections.

Surrounding the central lens are six additional lenses, each equipped with a 10 W RGBW LED. These create the second effect: as the entire lens assembly rotates, the beams are continuously redirected, producing a dynamic flower effect in haze.

As a third effect, an outer ring of 24 colored LEDs provides additional visual possibilities. These can create a colored frame or be used for various animation effects.

This results in three distinct effects that can be freely combined to create versatile and dynamic light shows.

Features:

- 1 LED 60 W COB (chip-on-board) cold white (CW)
- 6 LEDs 10 W SMD 5050 4in1 RGBW
- Positioning within 540° PAN, 180° TILT
- Exact positioning (16 bit resolution)
- Lens rotation
- Dimmer
- Spot effect; flower effect
- Color wheel with 7 dichroic filters plus open
half colors selectable
- Gobo wheel with static gobos, 7 gobos and open
shake effect

Logistic

EAN / GTIN: 4026397754957

Weight: 4,60 kg

Length: 0.34 m

Width: 0.26 m

Height: 0.24 m

- Control via stand-alone; sound to light via microphone; DMX; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional); master/slave function
- With a beam angle of 14° spot
- With omega bracket
- 4 digit 7-segment LED display
- 2 Rugged carrying handles
- Rubber feet
- Flicker-free
- The device is cooled by temperature-controlled fan at the head; low-noise cooling fan at the base
- For application areas such as: Clubs/dancing school; wedding/gala/events; party room; stage; mobile djs / entertainer; restaurants, bars and hotels
- Application possibility: Standing; suspended
- Can be operated in 16; 26 CH mode

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	145 W
Protection class:	Protection class I
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug
Fuse:	5 x 20 mm, T 2 A fuse replaceable
Lamp type:	LED lamp
LED type:	1 x 60 W COB (chip-on-board) cold white (CW) 6 x 10 W SMD 5050 4in1 RGBW 24 x 0.2 W SMD 5050 3in1 RGB (homogenous color mix)
Max. TILT movement:	180° exact positioning (16 bit resolution)
Max. PAN movement:	540° exact positioning (16 bit resolution)
Flash rate:	1.5 - 17 Hz
Equipment:	Lens rotation
Color generation:	Color wheel with 7 dichroic filters plus open Half colors selectable
Gobos:	Gobo wheel with static gobos, 7 gobos and open Shake effect
DMX channels:	16; 26
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	Temperature-controlled fan at the head Low-noise cooling fan at the base
Control:	Stand-alone; sound to light via microphone; DMX; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional); master/slave function
Fixtures available for:	Light´J; Light Captain; Colorchief
Projection:	Flicker-free
PWM frequency:	10600 Hz
DMX fail mode:	Hold; blackout
Beam angle:	14° spot

Beam angle (1/2 peak):	Spot 14°
Beam angle (1/10 peak):	Spot 14°
Housing color:	Black
Attachment system:	Omega bracket
Display type:	4 digit 7-segment LED display
USB port:	Type A
Carrying handle:	2 pc/pcs
Transport aid:	Rubber feet
Diameter mounting holes:	1 x Ø11mm
Material:	Plastic
Dimensions:	Width: 23.0 cm Depth: 17.5 cm Height: 31.0 cm
Weight:	4.15 kg
Noise classification:	Class 2 (slight noise)

Scope of delivery:

1 x moving light
 1 x user manual
 1 x power cord
 1 x omega bracket