

EUROLITE LED TMH-B60 Moving Head Beam

Moving moving head with 60 W COB LED in RGBW

Art. No.: 51786082

GTIN: 4026397710472



Features:

- Compact lightweight
- 1 LED 60 W COB (chip-on-board) 4in1 RGBW (homogenous color mix)
- Positioning within 540° PAN, 180° TILT
- Dimmer electronic; Motion macros adjustable
- Beam effect; strobe effect
- 4 integrated show programs
- Can be operated in 12; 14 CH mode
- The device is cooled by cooling fan
- Control via stand-alone; sound to light via microphone; master/slave function; DMX; QuickDMX via USB (optional); CRMX by LumenRadio via USB (optional); W-DMX by wireless solution via USB (optional)
- Flicker-free
- With a beam angle of 2°
- 4 digit 7-segment LED display
- Rubber feet
- For application areas such as: Clubs/dancing school; wedding/gala/events; party room; mobile djs / entertainer
- Application possibility: Standing; suspended

Logistic

EAN / GTIN: 4026397710472

Weight: 3,65 kg

Length: 0.29 m

Width: 0.22 m

Height: 0.27 m

Technical specifications:

Power supply: 100-240 V AC, 50/60 Hz

Power consumption: 60 W

Protection class: Protection class I

Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Fuse:	5 x 20 mm, T 1.5 A fuse replaceable
Lamp type:	LED lamp
LED type:	1 x 60 W COB (chip-on-board) 4in1 RGBW (homogenous color mix)
Max. TILT movement:	180° positioning
Max. PAN movement:	540° positioning
Flash rate:	2.5 - 16 Hz
DMX channels:	12; 14
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	Cooling fan
Control:	Stand-alone; sound to light via microphone; master/slave function; DMX; QuickDMX via USB (optional); CRMX by LumenRadio via USB (optional); W-DMX by wireless solution via USB (optional)
Fixtures available for:	Light Captain
Projection:	Flicker-free
PWM frequency:	2900 Hz
Beam angle:	2°
Beam angle (1/2 peak):	2°
Beam angle (1/10 peak):	5°
Illuminance in Lux (lx):	Red (R) 1m: 19079 lx, 3m: 3275 lx, 6m: 838 lx Green (G) 1m: 34129 lx, 3m: 5358 lx, 6m: 1372 lx Blue (B) 1m: 3925 lx, 3m: 1084 lx, 6m: 277 lx Cold white (CW) 1m: 48589 lx, 3m: 8089 lx, 6m: 2048 lx All 3m: 17330 lx, 6m: 4405 lx
Housing color:	Black
Display type:	4 digit 7-segment LED display
Transport aid:	Rubber feet
Dimensions:	Width: 17.5 cm Depth: 15.0 cm Height: 25.0 cm
Weight:	3.25 kg

Scope of delivery:

1 x moving light
 1 x user manual
 1 x power cord
 1 x omega bracket
 1 x safety eyelet