

EUROLITE LED TMH-S200 Moving Head Spot

LED moving head spot with color wheel, static & rot. gobo wheel, prism, frost, focus and zoom

Art. No.: 51786088

GTIN: 4026397677836



Features:

- 1 LED 200 W COB (chip-on-board) cold white (CW)
- Positioning within 540° PAN, 270° TILT
- Auto position correction (feedback)
- Exact positioning (16 bit resolution)
- Prism 3-fold rotating; frost filter; gobo wheel with rotating gobos; gobo wheel with static gobos; zoom motor driven; focus motor-driven; color wheel
- Dimmer electronic; Dimmer speed (step response) adjustable
- Color wheel with 9 dichroic filters plus open
half colors selectable, Rainbow effect with adjustable speed in both directions
- Gobo wheel with static gobos, 9 gobos and open
shake effect
- Gobo wheel with rotating gobos, 7 gobos and open
shake effect
- Slot-in gobo system for easy gobo replacement
- Gobos changeable
- Integrated show programs
- Can be operated in 17 CH mode
- The device is cooled by cooling fan
- Control via stand-alone; DMX; master/slave function; sound to light via microphone; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
- Flicker-free
- With a beam angle of 8° - 22°
- Multicolor LCD display
- Mains input and output for power linking up to 8 units
- For application areas such as: Clubs/dancing school; wedding/gala/events; stage; rental
- Application possibility: Standing; suspended

Logistic

EAN / GTIN: 4026397677836

Weight: 16,30 kg

Length: 0.51 m

Width: 0.42 m

Height: 0.42 m

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	250 W
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Power output:	P-Con (grey), mounting version
Fuse:	5 x 20 mm, T 3.15 A fuse replaceable
Lamp type:	LED lamp
LED type:	1 x 200 W COB (chip-on-board) cold white (CW)
Max. TILT movement:	270° exact positioning (16 bit resolution) auto position correction (feedback)
Max. PAN movement:	540° exact positioning (16 bit resolution) auto position correction (feedback)
Flash rate:	1 - 18 Hz
Equipment:	Prism 3-fold rotating; frost filter; gobo wheel with rotating gobos; gobo wheel with static gobos; zoom motor driven; focus motor-driven; color wheel
Color generation:	Color wheel with 9 dichroic filters plus open Half colors selectable, Rainbow effect with adjustable speed in both directions
Gobos:	Gobo wheel with static gobos, 9 gobos and open Shake effect Gobo wheel with rotating gobos, 7 gobos and open Outside diameter 19.5mm Image diameter 15mm Shake effect Slot-in gobo system for easy gobo replacement Gobos changeable
DMX channels:	17
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	Cooling fan
Control:	Stand-alone; DMX; master/slave function; sound to light via microphone; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
Fixtures available for:	Light Captain
Projection:	Flicker-free
Beam angle:	8° - 22°
Beam angle (1/2 peak):	8 - 22°
Beam angle (1/10 peak):	8 - 22°
Illuminance in Lux (lx):	Narrow cold white (CW) 3m: 22622 lx, 6m: 6278 lx Wide cold white (CW) 1m: 31619 lx, 3m: 4309 lx, 6m: 1112 lx
Housing color:	Black

Display type:	Multicolor LCD display
Dimensions:	Width: 30.5 cm Depth: 33.0 cm Height: 51.5 cm
Weight:	14.70 kg
Noise classification:	Class 3 (clearly perceptible sounds)

Scope of delivery:

1 x moving light
1 x user manual
1 x power cord
2 x omega bracket