

## EUROLITE LED TSL-200 Scan COB

Scanner with 20 W COB LED, rotating gobos and color wheel

Art. No.: 51786123

GTIN: 4026397390742



### Features:

- Equipped with a 20 W COB LED
- Long LED life
- Comparable to the light output of a 250 W halogen lamp
- DMX-controlled operation or stand-alone operation with Master/Slave function (up to 4 slaves)
- 14 motion macros can be called up via DMX controller
- Microphone-sensitivity adjustable via rotary-control
- Fuzzy sound control: program continues automatically during periods without music or bass-beat
- Strobe effect with 1-18 flashes per second
- Strobe effect with adjustable speed
- Random strobe effect
- Manual focus
- Dimmer
- Small and portable
- Lightbeam with 13° radiation angle
- Control board with 4-digit display for adjusting the DMX-starting address, Pan/Tilt-Reverse
- 6.3 mm jack socket for remote control
- Blackout, gobos, colors and Auto/Manual Mode applicable in Stand Alone mode via optional EUROLITE RC-1 remote control
- Advantages of LED technology: long life, low power consumption, minimal heat emission, defacto maintenance free with brilliant light radiation
- DMX control via any standard DMX controller
- 1 LED 20 W COB (chip-on-board) cold white (CW)
- Focus manual
- Gobo effect

### Logistic

EAN / GTIN: 4026397390742

Weight: 7,20 kg

Length: 0.48 m

Width: 0.28 m

Height: 0.30 m

- Color wheel with 7 dichroic filters plus open<BR>rainbow effect with adjustable speed in both directions
- Gobo wheel with rotating gobos, 7 gobos and open<BR>shake effect
- Can be operated in 9 CH mode
- The device is cooled by cooling fan
- Control via DMX; stand-alone; sound to light via microphone
- With a beam angle of 13°
- 4 digit 7-segment LED display

## Technical specifications:

|                         |                                                                                                                  |
|-------------------------|------------------------------------------------------------------------------------------------------------------|
| Power supply:           | 230 V AC, 50 Hz                                                                                                  |
| Power consumption:      | 70 W                                                                                                             |
| Protection class:       | Protection class I                                                                                               |
| Power connection:       | Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)                 |
| Lamp type:              | LED lamp                                                                                                         |
| LED type:               | 1 x 20 W COB (chip-on-board) cold white (CW)                                                                     |
| Flash rate:             | 0 - 18 Hz                                                                                                        |
| Equipment:              | Focus manual                                                                                                     |
| Color generation:       | Color wheel with 7 dichroic filters plus open<br>Rainbow effect with adjustable speed in both directions         |
| Gobos:                  | Gobo wheel with rotating gobos, 7 gobos and open<br>Outside diameter 25mm<br>Image diameter 20mm<br>Shake effect |
| DMX channels:           | 9                                                                                                                |
| DMX input:              | 3-pin XLR (M) mounting version                                                                                   |
| DMX output:             | 3-pin XLR (F) mounting version                                                                                   |
| Cooling:                | Cooling fan                                                                                                      |
| Control:                | DMX; stand-alone; sound to light via microphone                                                                  |
| Fixtures available for: | LED PC-Control 512; EASY SHOW 1; Light Captain                                                                   |
| Beam angle:             | 13°                                                                                                              |
| Beam angle (1/2 peak):  | 13°                                                                                                              |
| Housing color:          | Black                                                                                                            |
| Display type:           | 4 digit 7-segment LED display                                                                                    |
| Dimensions:             | Width: 20.5 cm<br>Depth: 39 cm<br>Height: 30 cm                                                                  |
| Weight:                 | 6.20 kg                                                                                                          |

## Scope of delivery:

- 1 x light effect
- 1 x user manual
- 1 x power cord