

EUROLITE LED TSL-1000 Scan MK2

Scanner with 100 W LED, rotating gobos, 3-facet prism, color wheel and motorized focus

Art. No.: 51786126

GTIN: 4026397699104



List price: 510.51 €

incl. 19% VAT.

Features:

- Note: The macro programs of the predecessor model (no. 51786122) are not identical, therefore no synchronous master/slave operation is possible between these devices.
 - 1 LED 100 W COB (chip-on-board) cold white (CW)
 - Positioning within 160° PAN, 50° TILT
 - Exact positioning (16 bit resolution)
 - Focus motor-driven; color wheel; gobo wheel with rotating gobos; prism 3-fold
 - Dimmer electronic
 - Gobo effect; strobe effect
 - Color wheel with 8 dichroic filters plus open
half colors selectable, Rainbow effect with adjustable speed in both directions
 - Gobo wheel with rotating gobos, 7 gobos and open
shake effect
 - Gobos changeable
 - Slot-in gobo system for easy gobo replacement
 - Integrated show programs
 - Can be operated in 10; 15 CH mode
 - The device is cooled by cooling fan
 - Control via stand-alone; DMX; master/slave function; sound to light via microphone
 - Flicker-free
 - With a beam angle of 20°
 - OLED display
 - Rubber feet
 - Mains input and output for power linking up to 8 units
 - For application areas such as: Clubs/dancing school; wedding/gala/events; mobile djs / entertainer; stage; restaurants, bars and hotels
 - Application possibility: Standing; suspended; on stand
- safety eyelet**

Logistic

EAN / GTIN: 4026397699104

Weight: 6,60 kg

Length: 0.50 m

Width: 0.31 m

Height: 0.25 m

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	110 W
Protection class:	Protection class I
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Power output:	P-Con (grey), mounting version
Fuse:	5 x 20 mm, T 4 A fuse replaceable
Lamp type:	LED lamp
LED type:	1 x 100 W COB (chip-on-board) cold white (CW)
Max. TILT movement:	50° exact positioning (16 bit resolution)
Max. PAN movement:	160° exact positioning (16 bit resolution)
Flash rate:	1 - 25 Hz
Equipment:	Focus motor-driven; color wheel; gobo wheel with rotating gobos; prism 3-fold
Color generation:	Color wheel with 8 dichroic filters plus open Half colors selectable, Rainbow effect with adjustable speed in both directions
Gobos:	Gobo wheel with rotating gobos, 7 gobos and open Outside diameter 23.9mm Image diameter 18mm Shake effect Gobos changeable Slot-in gobo system for easy gobo replacement
DMX channels:	10; 15
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	Cooling fan
Control:	Stand-alone; DMX; master/slave function; sound to light via microphone
Fixtures available for:	Light´J; Light Captain; EASY SHOW 2; EASY SHOW 3
Projection:	Flicker-free
Beam angle:	20°
Beam angle (1/2 peak):	20°
Color temperature:	8000K
Illuminance in Lux (lx):	Cold white (CW) 1m: 35679 lx, 3m: 4265 lx, 6m: 1055 lx
Housing color:	Black
Display type:	OLED display
Transport aid:	Rubber feet
Material:	Metal; plastic
Dimensions:	Width: 25.1 cm Depth: 14.1 cm Height: 37.7 cm

Weight:	5.75 kg
Noise classification:	Class 2 (slight noise)
Cable construction:	3 x 1.0 mm² H05VV-F
Diameter mounting holes:	3 x Ø10mm
Material:	Metal, 3 mm
Material:	Metal
Ring diameter:	Outside: 23 mm Inside: 11 mm
Thread:	M6 thread

Scope of delivery:

- 1 x light effect
- 1 x power cord
- 1 x safety eyelet
- 1 x user manual