

## EUROLITE LED TSL-1500 Scan

Scanner with 150 W LED, rotating gobos and 4-facet prism, color wheel and motorized focus

Art. No.: 51786127

GTIN: 4026397714456



### Features:

- 1 LED 150 W COB (chip-on-board) cold white (CW)
- Positioning within 180° PAN, 70° TILT
- Focus motor-driven; color wheel; gobo wheel with rotating gobos; prism 4-fold rotating
- Dimmer electronic
- Gobo effect; strobe effect
- Color wheel with 8 dichroic filters plus open<BR>half colors selectable, Rainbow effect with adjustable speed in both directions
- Gobo wheel with rotating gobos, 7 gobos and open<BR>shake effect
- Gobos changeable
- Slot-in gobo system for easy gobo replacement
- 9 integrated show programs
- Can be operated in 13 CH mode
- The device is cooled by temperature-controlled fan
- Control via stand-alone; sound to light via microphone; master/slave function; DMX; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
- Flicker-free
- With a beam angle of 11°
- OLED display
- Rubber feet
- Mains input and output for power linking up to 8 units
- For application areas such as: Clubs/dancing school; wedding/gala/events; stage; mobile djs / entertainer; restaurants, bars and hotels
- Application possibility: Standing; suspended; on stand

### Logistic

EAN / GTIN: 4026397714456

Weight: 8,20 kg

Length: 0.60 m

Width: 0.30 m

Height: 0.25 m

## Technical specifications:

|                          |                                                                                                                                                                                           |
|--------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Power supply:            | 100-240 V AC, 50/60 Hz                                                                                                                                                                    |
| Power consumption:       | 175 W                                                                                                                                                                                     |
| Protection class:        | Protection class I                                                                                                                                                                        |
| Power connection:        | Mains input via P-Con (blue), mounting version power supply cord with safety plug                                                                                                         |
| Power output:            | P-Con (grey), mounting version                                                                                                                                                            |
| Fuse:                    | 5 x 20 mm, F 5 A fuse replaceable                                                                                                                                                         |
| Lamp type:               | LED lamp                                                                                                                                                                                  |
| LED type:                | 1 x 150 W COB (chip-on-board) cold white (CW)                                                                                                                                             |
| Max. TILT movement:      | 70° positioning                                                                                                                                                                           |
| Max. PAN movement:       | 180°                                                                                                                                                                                      |
| Flash rate:              | 0.5 - 21 Hz                                                                                                                                                                               |
| Equipment:               | Focus motor-driven; color wheel; gobo wheel with rotating gobos; prism 4-fold rotating                                                                                                    |
| Color generation:        | Color wheel with 8 dichroic filters plus open Half colors selectable, Rainbow effect with adjustable speed in both directions                                                             |
| Gobos:                   | Gobo wheel with rotating gobos, 7 gobos and open<br>Outside diameter 19.8mm<br>Image diameter 17mm<br>Shake effect<br>Gobos changeable<br>Slot-in gobo system for easy gobo replacement   |
| DMX channels:            | 13                                                                                                                                                                                        |
| DMX input:               | 3-pin XLR (M) mounting version                                                                                                                                                            |
| DMX output:              | 3-pin XLR (F) mounting version                                                                                                                                                            |
| Cooling:                 | Temperature-controlled fan                                                                                                                                                                |
| Control:                 | Stand-alone; sound to light via microphone; master/slave function; DMX; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional) |
| Fixtures available for:  | Light Captain                                                                                                                                                                             |
| Projection:              | Flicker-free                                                                                                                                                                              |
| Beam angle:              | 11°                                                                                                                                                                                       |
| Beam angle (1/2 peak):   | 11°                                                                                                                                                                                       |
| Color temperature:       | 10000K                                                                                                                                                                                    |
| Illuminance in Lux (lx): | Cold white (CW) 3m: 15649 lx, 6m: 4147 lx                                                                                                                                                 |
| Housing color:           | Black                                                                                                                                                                                     |
| Display type:            | OLED display                                                                                                                                                                              |
| Transport aid:           | Rubber feet                                                                                                                                                                               |
| Dimensions:              | Width: 33.5 cm<br>Depth: 16.5 cm<br>Height: 47 cm                                                                                                                                         |
| Weight:                  | 7.05 kg                                                                                                                                                                                   |

## Scope of delivery:

---

1 x device  
1 x user manual  
1 x power cord  
1 x safety eyelet