

EUROLITE LED TSL-350 Scan COB

Handy scanner with 60 W COB LED, gobo and color wheel

Art. No.: 51786150

GTIN: 4026397709414



List price: 355.81 €

incl. 19% VAT.

Features:

- Compact design
- 1 LED 60 W COB (chip-on-board) cold white (CW)
- Positioning within
- Color wheel; gobo wheel with rotating gobos; focus manual
- Dimmer electronic
- Color wheel with 7 dichroic filters plus open
half colors selectable, Rainbow effect with adjustable speed
- Gobo wheel with rotating gobos, 7 gobos and open
gobos changeable
- Slot-in gobo system for easy gobo replacement
- Shake effect
- Integrated show programs
- Can be operated in 10 CH mode
- The device is cooled by cooling fan
- Control via stand-alone; DMX; QuickDMX via USB (optional); master/slave function; sound to light via microphone; W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
- Flicker-free
- With a beam angle of 11°
- LCD display
- Rubber feet
- Available in various colors
- For application areas such as: Clubs/dancing school; party room; mobile djs / entertainer
- Application possibility: Standing; suspended; on stand

Logistic

EAN / GTIN: 4026397709414

Weight: 3,60 kg

Length: 0.40 m

Width: 0.22 m

Height: 0.21 m

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	70 W
Protection class:	Protection class I
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Fuse:	5 x 20 mm, T 1.5 A fuse replaceable
Lamp type:	LED lamp
LED type:	1 x 60 W COB (chip-on-board) cold white (CW)
Equipment:	Color wheel; gobo wheel with rotating gobos; focus manual
Color generation:	Color wheel with 7 dichroic filters plus open Half colors selectable, Rainbow effect with adjustable speed
Gobos:	Gobo wheel with rotating gobos, 7 gobos and open Outside diameter 14mm Image diameter 10mm Gobos changeable Slot-in gobo system for easy gobo replacement Shake effect
DMX channels:	10
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	Cooling fan
Control:	Stand-alone; DMX; QuickDMX via USB (optional); master/slave function; sound to light via microphone; W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
Fixtures available for:	Light Captain; Light J; EASY SHOW 2; EASY SHOW 3
Projection:	Flicker-free
Beam angle:	11°
Beam angle (1/2 peak):	11°
Illuminance in Lux (lx):	Cold white (CW) 1m: 12034 lx, 3m: 1489 lx, 6m: 388 lx
Housing color:	Black
Display type:	LCD display
Transport aid:	Rubber feet
Dimensions:	Width: 16.0 cm Depth: 15.0 cm Height: 33.0 cm
Weight:	3.22 kg

Scope of delivery:

1 x moving light
1 x user manual
1 x power cord
1 x mounting bracket
3 x gobos