

EUROLITE TMH BSW-380 Moving-Head Beam/Spot/Wash

Art. No.: 51786850

Beam/spot/wash moving head with 371 W discharge lamp, color wheel, gobo wheels, prisms, frost, focus and zoom

GTIN: 4026397701142



Features:

- Light source: Osram Sirius HRI 371W discharge lamp
- Lamp installed and adjusted ex factory
- Additional frost filter provides a wide, soft and homogeneous light
- Positioning within 540° PAN, 230° TILT
- Auto position correction (feedback)
- Exact positioning (16 bit resolution)
- Exact 16 bit resolution at zoom, focus
- Prism 16-fold; prism 8-fold rotating; prism 16-fold rotating; gobo wheel with static gobos; gobo wheel with rotating gobos; focus motor-driven; zoom motor driven; frost filter; Dimmer
- Color animations; patterns
- Beam effect; spot effect; wash effect
- Color wheel with 13 dichroic filters plus open
rainbow effect with adjustable speed in both directions; half colors selectable, Rainbow effect with adjustable speed in both directions
- Gobo wheel with rotating gobos, 7 gobos and open
shake effect
- Slot-in gobo system for easy gobo replacement
- Gobos changeable
- Gobo wheel with static gobos, 11 gobos and open
shake effect
- Gobo wheel with static gobos, 5 gobos and open
shake effect
- Integrated show programs
- Can be operated in 22; 26 CH mode
- The device is cooled by cooling fan
- Control via stand-alone; DMX; sound to light via microphone; master/slave function; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMx by LumenRadio via USB (optional)
- With a beam angle of 4° - 35° spot
- Multicolor LCD display,
with battery buffering for easy controlling

Logistic

EAN / GTIN: 4026397701142

Weight: 25,30 kg

Length: 0.54 m

Width: 0.50 m

Height: 0.64 m

- Mains input and output for power linking up to 4 units
- OSRAM bulb included
- For application areas such as: Clubs/dancing school; stage; rental
- Application possibility: Standing; suspended

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	490 W
Protection class:	Protection class I
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Power output:	P-Con (grey), mounting version
Fuse:	5 x 20 mm, T 8 A
Lamp type:	Discharge lamp
Max. TILT movement:	230° exact positioning (16 bit resolution) auto position correction (feedback)
Max. PAN movement:	540° exact positioning (16 bit resolution) auto position correction (feedback)
Flash rate:	1 - 18 Hz
Equipment:	Prism 16-fold; prism 8-fold rotating; prism 16-fold rotating; gobo wheel with static gobos; gobo wheel with rotating gobos; focus motor-driven; zoom motor driven; frost filter; Dimmer
Color generation:	Color wheel with 13 dichroic filters plus open Rainbow effect with adjustable speed in both directions; half colors selectable, Rainbow effect with adjustable speed in both directions
Gobos:	Gobo wheel with rotating gobos, 7 gobos and open Shake effect Outside diameter 22.5mm Image diameter 12mm Slot-in gobo system for easy gobo replacement Gobos changeable Gobo wheel with static gobos, 11 gobos and open Shake effect Gobo wheel with static gobos, 5 gobos and open Shake effect
DMX channels:	22; 26
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	Cooling fan
Control:	Stand-alone; DMX; sound to light via microphone; master/slave function; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
Fixtures available for:	Light Captain
Beam angle:	4° - 35° spot
Beam angle (1/2 peak):	Spot 4 - 35°
Beam angle (1/10 peak):	Spot 4 - 35°

Housing color:	Black
Display type:	Multicolor LCD display battery buffering
Use of brands:	OSRAM bulb included
Dimensions:	Width: 39.5 cm Depth: 30.5 cm Height: 63.0 cm
Weight:	22.70 kg
Noise classification:	Class 3 (clearly perceptible sounds)

- Scope of delivery:**
- 1 x moving light
 - 1 x user manual
 - 1 x power cord
 - 2 x omega bracket