

EUROLITE LED SL-1000 MFZ DMX Search Light incl. flight case

Motorized DMX follow spot with cold white 1000 W LED, zoom & focus for long distances

Art. No.: 51787336

GTIN: 4026397727289



Features:

- Manual control via movable control panel with buttons and faders
- 1 LED 1000 W COB (chip-on-board) cold white (CW)
- Color wheel; iris stepless; frost filter; zoom motor driven; focus motor-driven
- Dimmer electronic
- Strobe effect
- Color wheel with 7 dichroic filters plus open half colors selectable
- Can be operated in 8 CH mode
- The device is cooled by cooling fan
- Control via stand-alone; master/slave function; DMX
- Flicker-free
- With a beam angle of 2° - 7°
- Direct color temperature selection for 4 preset values
- With mounting bracket
- Monochrome LCD display
- Suitable for a range of use from 75 to 200 meters
- For application areas such as: Wedding/gala/events; stage; theater; rental
- Application possibility: On stand
- For further information about this product, please refer to the Data Sheet under "Downloads"

Logistic

EAN / GTIN: 4026397727289

Weight: 83,24 kg

Length: 1.31 m

Width: 0.64 m

Height: 0.73 m

Bulky product

Technical specifications:

Power supply: 100-240 V AC, 50/60 Hz

Power consumption: 1000 W

Power connection:	Mains input via IP T-Con (M) mounting version power supply cord with safety plug
Fuse:	5 x 20 mm, T 8 A fuse replaceable
Lamp type:	LED lamp
LED type:	1 x 1000 W COB (chip-on-board) cold white (CW)
Flash rate:	0.8 - 12 Hz
Equipment:	Color wheel; iris stepless; frost filter; zoom motor driven; focus motor-driven
Color generation:	Color wheel with 7 dichroic filters plus open Half colors selectable
DMX channels:	8
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	Cooling fan
Control:	Stand-alone; master/slave function; DMX
Projection:	Flicker-free
PWM frequency:	16800 Hz
Beam angle:	2° - 7°
Beam angle (1/2 peak):	2 - 7°
Beam angle (1/10 peak):	2 - 7°
Housing color:	Black
Attachment system:	Mounting bracket
Display type:	Monochrome LCD display
Range of use:	75m - 200m
Dimensions:	Length: 113.0 cm Width: 32.0 cm Height: 46.0 cm
Weight:	82.65 kg
Noise classification:	Class 2 (slight noise)
Weight:	34 kg
Gobos:	Outside diameter 39.8mm Image diameter 23.5mm

Scope of delivery:

1 x spotlight
 1 x controller
 1 x user manual
 1 x power cord
 1 x gobo holder
 1 x case
 1 x XLR cable