EUROLITE LED IP LP-120 Logo Projector

Outdoor logo projector with 4 rotating, interchangeable gobos and a weekly clock timer

Art. No.: 51799301

GTIN: 4026397758368











List price: 831.81 €

incl. 19% VAT.

Description:

This weatherproof logo projector comes with three built-in colored motifs and three included black-and-white gobos for replacement. It can also be fitted with custom glass gobos. The outer diameter of the gobos is 25.8 mm, while the motif can be up to 20 mm in size. Replacing the gobos is simple and user-friendly.

The gobos can rotate continuously and feature precise indexing, ensuring they are always correctly aligned.

Equipped with a 120 W LED, the projector delivers strong output. It can be controlled via DMX or used in stand-alone mode. In addition, it features an integrated timer function that allows you to define exactly which gobo is displayed, in which position or rotation, at specific times and days of the week.

Features:

- 1 LED 120 W COB (chip-on-board) cold white (CW)
- Suitable for outdoor use IP65
- With a beam angle of 17°
- Built-in intelligent controller for precise timing of gobo switching, gobo rotation and brightness
- 3 colored glass gobos (design: fireworks, snowflakes and Halloween) are pre-installed in the gobo wheel upon delivery. 3 b/w glass gobos (design: Merry Christmas, stars and smiley) are included for the fourth slot in the gobo wheel
- Use of custom gobos is possible
- Gobo wheel with rotating gobos, 4 gobos
gobos changeable
- Gobo indexable
- Slot-in gobo system for easy gobo replacement
- Dimmer; dimmer curves; pulse-width modulation adjustable

Logistic

EAN / GTIN: 4026397758368
Weight: 7,20 kg
Length: 0.40 m
Width: 0.28 m
Heigth: 0.33 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

- Very quiet working noise
- The device is cooled by temperature-controlled fan
- Flicker-free
- With mounting bracket
- Monochrome OLED display
- Built with SEETRONIC connector
- With pressure compensation membrane
- For application areas such as: Clubs/dancing school; wedding/gala/events; Trade fair and shop fitting; installation; restaurants, bars and hotels; rental; architecture; advertisement/Shop window
- Application possibility: Standing; suspended; on stand
- Can be operated in 3; 5; 7 CH mode
- Control via stand-alone; DMX; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional); master/slave function

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	100 W
IP classification:	IP65
Protection class:	Protection class I
Power connection:	Mains input via IP T-Con (M) mounting version power supply cord with safety plug
Cable construction:	3 x 1.5 mm² H07RN-F
Lamp type:	LED lamp
LED type:	1 x 120 W COB (chip-on-board) cold white (CW)
Flash rate:	1 - 35 Hz
Equipment:	Gobo wheel with rotating gobos
Gobos:	Gobo wheel with rotating gobos, 4 gobos Outside diameter 25.8mm Image diameter 20mm Gobos changeable Gobo indexable Shake effect Slot-in gobo system for easy gobo replacement Rainbow effect with adjustable speed in both directions
DMX channels:	3; 5; 7
DMX input:	3-pin XLR (M) mounting version IP
DMX output:	3-pin XLR (F) mounting version IP
Cooling:	1 x temperature-controlled fan
Control:	Stand-alone; DMX; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional); master/slave function
Projection:	Flicker-free
DMX fail mode:	Hold; blackout
Beam angle:	17°
Beam angle (1/2 peak):	17°
Beam angle (1/10 peak):	17°
Color temperature:	9700K
Housing color:	Black
Attachment system:	1x mounting bracket

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Display type:	Monochrome OLED display
USB port:	Type A
Diameter mounting holes:	1 x Ø12mm
Use of brands:	Built with SEETRONIC connector
Material:	Aluminum casting
Dimensions:	Length: 30 cm Width: 24 cm Height: 25.6 cm
Weight:	6.30 kg
Noise classification:	Class 1 (very slight noise, suitable for noise-sensitive environments) depending on mode used

Scope of delivery:

1 x device
1 x user manual
1 x power cord
3 x gobos
1 x spring washer

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.