

EUROLITE LED LP-100 Logo Projector MK2

Professional gobo projector with additional color wheel

Art. No.: 51799326

GTIN: 4026397745337



List price: 355.81 €

incl. 19% VAT.

Features:

- 1 LED 100 W COB (chip-on-board) cold white (CW)
- Gobos rotating; zoom manual; focus manual
- Dimmer electronic; color selection direct; Rotation speed adjustable; Rotation direction adjustable; program selection manual
- Gobo effect; spot effect
- Color wheel with 5 dichroic filters plus open
half colors selectable, Rainbow effect with adjustable speed in both directions
- Gobo wheel with rotating gobos
gobos changeable
- Gobo indexable
- 3 integrated show programs
- Can be operated in 5 CH mode
- The device is cooled by temperature-controlled fan
- Control via stand-alone; master/slave function; DMX; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
- Flicker-free
- With a beam angle of 12° - 25° spot
- Monochrome 4 digit 7-segment LED display
- Mains input and output for power linking up to 8 units
- For application areas such as: Stage; clubs/dancing school; decoration; wedding/gala/events; Trade fair and shop fitting; mobile djs / entertainer; restaurants, bars and hotels; theater; rental; video and photography; advertisement/Shop window
- Application possibility: Standing; suspended; on stand
- **mounting bracket**
- With double bracket

Logistic

EAN / GTIN: 4026397745337

Weight: 5,24 kg

Length: 0.42 m

Width: 0.21 m

Height: 0.20 m

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz 230V AC 1000 mA
Power consumption:	100 W
Protection class:	Protection class I
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Power output:	1 x P-Con (grey), mounting version Bypass
Fuse:	5 x 20 mm, T 3 A fuse replaceable
Lamp type:	LED lamp
LED type:	1 x 100 W COB (chip-on-board) cold white (CW)
Flash rate:	0.4 - 24 Hz
Equipment:	Gobos rotating; zoom manual; focus manual
Color generation:	Color wheel with 5 dichroic filters plus open Half colors selectable, Rainbow effect with adjustable speed in both directions
Gobos:	Gobo wheel with rotating gobos Outside diameter 32.6mm Image diameter 21mm Gobos changeable Gobo indexable
DMX channels:	5
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version Bypass
Cooling:	2 x temperature-controlled fan
Control:	Stand-alone; master/slave function; DMX; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
Fixtures available for:	Light Captain
Projection:	Flicker-free
PWM frequency:	24000 Hz
DMX fail mode:	Hold; blackout
Beam angle:	12° - 25° spot
Beam angle (1/2 peak):	Spot 12 - 14°
Beam angle (1/10 peak):	Spot 12 - 25°
Illuminance in Lux (lx):	Narrow cold white (CW) 1m: 133020 lx, 3m: 14449 lx, 6m: 3622 lx Wide cold white (CW) 1m: 43370 lx, 3m: 4970 lx, 6m: 1328 lx
Housing color:	Black matte
Display type:	1 x monochrome 4 digit 7-segment LED display
USB port:	1 x type A
Material:	Metal, painted
Dimensions:	Length: 31 cm Width: 20 cm Height: 29 cm

Weight:	4.67 kg
Noise classification:	Class 2 (slight noise)
Cable construction:	3 x 1.0 mm ² H05VV-F
Attachment system:	Ø 12mm Double bracket

Scope of delivery:

1 x device
1 x user manual
1 x power cord
1 x gobo holder
3 x gobos
2 x mounting bracket
2 x knurled screw
4 x washer