

## FUTURELIGHT CP-240 Controller

Compact DMX controller

Art. No.: 51834265

GTIN: 4026397194227



### Features:

- 240 control channels for 12 projectors with up to 20 channels
- 8 channel faders with two banks for direct control of 16 channels
- PAN/TILT encoders
- All channels freely assignable
- All channel faders and encoders can be inverted
- Fine PAN/TILT movements possible via fine button
- Fade Time fader for adjusting the step time
- Fade Time assignable to only PAN/TILT or all DMX channels
- 240 scenes on 30 banks can be programmed
- 30 programs with up to 8 scenes can be programmed
- 6 chasers with up to 240 scenes can be programmed
- Copy function for the scenes, programs and banks
- Blackout function
- Fogger button for direct fogger control
- Sound control via RCA socket
- Rack installation with 3 units

### Logistic

EAN / GTIN: 4026397194227

Weight: 2,95 kg

Length: 0.59 m

Width: 0.20 m

Height: 0.13 m

### Technical specifications:

Power supply: 230 V AC, 50 Hz

Power consumption: 5.00 W

Dimensions: Width: 48.3 cm  
Depth: 13.4 cm

|                             |                                                           |
|-----------------------------|-----------------------------------------------------------|
|                             | Height: 8.9 cm                                            |
|                             | via 9-12 V DC, 300 mA power unit included in the delivery |
| Number of control channels: | 240                                                       |
| Integrated programs:        | 30 with 8 scenes each                                     |
| Chasers:                    | 6 x 240 scenes                                            |
| Sound-control:              | via built-in microphone or via audio-input                |
| Audio-input:                | RCA                                                       |
| Audio-sensitivity:          | 0.1-1 V                                                   |
| DMX512 output:              | 3-pin XLR connector with polarity selector                |
| Dimensions (L x W x H):     | 483 x 134 x 90 mm                                         |
|                             | Rack installation with 3 u                                |
| Minimum mounting depth:     | 170 mm                                                    |
| Weight:                     | 2.5 kg                                                    |

**Scope of delivery:**

---