

FUTURELIGHT PLB-230 Moving Head

High performance beam with Osram Sirius HRI 230 W lamp and LED ring with RGB color mixture

Art. No.: 51838951

GTIN: 4026397484120



The article is no longer in our assortment.

Features:

- With integrated wireless receiver for WDMX operation (Wireless Solution - made in Sweden)
- Effect wheel with rotating 3-facet prism and 8-facet prism and frost filter
- Strobe effect with adjustable speed
- Random strobe effect
- Electronic dimmer (0-100%)
- Exact positioning via 16 bit PAN/TILT movement resolution
- Automatic position correction
- PAN angle switchable between 540° and 630°
- Number of scenes in Program Run can be changed individually
- The scenes can be modified via the Control Board or via an external controller and loaded into the memory
- Software upload by optional accessories via DMX link
- With already installed Osram Sirius HRI 230 W lamp
- 12 LEDs 3 W 3in1 RGB
- PAN angle switchable between 540° and 630°
- Auto position correction (feedback)
- Exact positioning (16 bit resolution)
- Gobo wheel with rotating gobos; focus motor-driven
- Gobo effect
- Color wheel with 14 dichroic filters plus open
rainbow effect with adjustable speed in both directions
- Gobo wheel with rotating gobos, 8 gobos and open
shake effect
- Gobos changeable
- Slot-in gobo system for easy gobo replacement
- Can be operated in 17; 19; 21; 24 CH mode
- The device is cooled by temperature-controlled fan

Logistic

EAN / GTIN: 4026397484120

Weight: 18,10 kg

Length: 0.61 m

Width: 0.44 m

Height: 0.36 m

- Control via RDM; DMX; stand-alone; W-DMX by wireless solution; sound to light via microphone
- With a beam angle of 1.3°

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	325.00 W
Power connection:	Mains input via PowerCON (blue), mounting version power supply cord with safety plug
Lamp type:	Discharge lamp
LED type:	12 x 3 W 3in1 RGB
Max. TILT movement:	270° exact positioning (16 bit resolution) auto position correction (feedback)
Max. PAN movement:	540°, 630° exact positioning (16 bit resolution) auto position correction (feedback)
Flash rate:	0 - 20 Hz
Equipment:	Gobo wheel with rotating gobos; focus motor-driven
Color generation:	Color wheel with 14 dichroic filters plus open Rainbow effect with adjustable speed in both directions
Gobos:	Gobo wheel with rotating gobos, 8 gobos and open Outside diameter 14mm Image diameter 6mm Shake effect Gobos changeable Slot-in gobo system for easy gobo replacement
DMX channels:	17; 19; 21; 24
DMX input:	1 x 3-pin XLR (M) mounting version 1 x 5-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version 1 x 5-pin XLR (F) mounting version
Cooling:	Temperature-controlled fan
Control:	RDM; DMX; stand-alone; W-DMX by wireless solution; sound to light via microphone
Fixtures available for:	LED PC-Control 512; Light Captain; Light´J
Carrier frequency:	2.4 GHz
Beam angle:	1.3°
Beam angle (1/2 peak):	1.3°
Housing color:	Black
Dimensions:	Width: 25 cm Depth: 42.4 cm Height: 34.3 cm
Weight:	16.20 kg
Noise classification:	Class 3 (clearly perceptible sounds)

Scope of delivery:
