

## FUTURELIGHT Color Mega Wave.i LED Moving Bar

4in1 moving head with two separately tiltable LED bars and six beams with 40 W COB LEDs

Art. No.: 51839010

GTIN: 4026397545869



**The article is no longer in our assortment.**

### Features:

- With Infinity function for unlimited PAN movement
- TILT movement for each LED bar separately and steplessly adjustable
- Equipped with six 40 W LEDs with RGBW colors
- Upgrade via optional wireless receiver module for WDMX operation (Wireless Solution - made in Sweden)
- 17, 18, 20 or 39 DMX channels selectable
- Each LED can be controlled individually
- Narrow illumination angle
- Functions: built-in programs, shutter sequences, color presets for each LED independently controllable, countless RGBW colors, dimmer, strobe effect with variable speed, sound-control, Master/Slave operation
- Automatic position correction
- Exact positioning via 16 bit PAN/TILT movement resolution
- Random strobe effect
- DMX-controlled operation or stand-alone operation with Master/Slave function
- Control board with graphic LCD and foil-keyboard for adjusting the DMX-starting address, PAN/TILT reverse, reset
- The scenes can be modified via the Control Board or via an external controller and loaded into the memory
- Number of scenes can be changed individually
- Software upload by optional accessories via DMX link
- ESDC function (Easy Service Data Check) with battery-buffered control board for operation time readouts etc. (the Li-Ion battery 3.7V, AAA, 10440 is not included)
- Switch-mode power supply for operation between 100 and 240 Volts
- Power connection via Neutrik PowerCon jack and included power cable
- Feed-through output allows to power up to 8 devices

### Logistic

EAN / GTIN: 4026397545869

Weight: 14,90 kg

Length: 0.61 m

Width: 0.40 m

Height: 0.33 m

- DMX control via every standard DMX controller
- 6 LEDs 40 W COB (chip-on-board) 4in1 RGBW (homogenous color mix)
- Auto position correction (feedback)
- Exact positioning (16 bit resolution)
- Fan effect
- Can be operated in 17; 18; 20; 39 CH mode
- The device is cooled by temperature-controlled fan
- Control via RDM; DMX; stand-alone; W-DMX by wireless solution; sound to light via microphone
- Flicker-free
- With a beam angle of 7°

## Technical specifications:

|                          |                                                                                                                                                                                                  |
|--------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Power supply:            | 100-240 V AC, 50/60 Hz                                                                                                                                                                           |
| Power consumption:       | 200 W                                                                                                                                                                                            |
| Power connection:        | Mains input via PowerCON (blue), mounting version power supply cord with safety plug (provided)                                                                                                  |
| Power output:            | 1 x PowerCON (grey), mounting version                                                                                                                                                            |
| Lamp type:               | LED lamp                                                                                                                                                                                         |
| LED type:                | 6 x 40 W COB (chip-on-board) 4in1 RGBW (homogenous color mix)                                                                                                                                    |
| Max. TILT movement:      | 240° exact positioning (16 bit resolution) auto position correction (feedback)                                                                                                                   |
| Max. PAN movement:       | Exact positioning (16 bit resolution) plus infinity auto position correction (feedback)                                                                                                          |
| Flash rate:              | 0 - 20 Hz                                                                                                                                                                                        |
| DMX channels:            | 17; 18; 20; 39                                                                                                                                                                                   |
| DMX input:               | 1 x 5-pin XLR (M) mounting version<br>1 x 3-pin XLR (M) mounting version                                                                                                                         |
| DMX output:              | 1 x 5-pin XLR (F) mounting version<br>1 x 3-pin XLR (F) mounting version                                                                                                                         |
| Cooling:                 | Temperature-controlled fan                                                                                                                                                                       |
| Control:                 | RDM; DMX; stand-alone; W-DMX by wireless solution; sound to light via microphone                                                                                                                 |
| Fixtures available for:  | LED PC-Control 512                                                                                                                                                                               |
| Projection:              | Flicker-free                                                                                                                                                                                     |
| Beam angle:              | 7°                                                                                                                                                                                               |
| Beam angle (1/2 peak):   | 7°                                                                                                                                                                                               |
| Beam angle (1/10 peak):  | 7°                                                                                                                                                                                               |
| Illuminance in Lux (lx): | Red (R) 3m: 3209 lx, 6m: 1777 lx<br>Green (G) 1m: 0 lx, 3m: 6717 lx, 6m: 2801 lx<br>Blue (B) 3m: 820 lx, 6m: 421 lx<br>Cold white (CW) 3m: 6993 lx, 6m: 3347 lx<br>All 3m: 16094 lx, 6m: 7504 lx |
| Housing color:           | Black                                                                                                                                                                                            |
| Dimensions:              | Width: 25 cm<br>Depth: 53.8 cm<br>Height: 34.2 cm                                                                                                                                                |
| Weight:                  | 12.85 kg                                                                                                                                                                                         |

**Scope of delivery:**

---