

## FUTURELIGHT Profile 200, 20-45°

PRO profile spotlight, warm white 200 W LED, zoom, CRI >90, extremely quiet

Art. No.: 51840915

GTIN: 4026397625714



**List price: 1188.81 €**

incl. 19% VAT.

### Features:

- Glass front lens
- 1 LED 200 W COB (chip-on-board) warm white (WW)
- Focus manual; zoom manual
- Dimmer electronic; Dimmer speed (step response) adjustable
- Strobe effect
- Can be operated in 1; 2 CH mode
- The device is cooled by low-noise cooling fan
- Control via DMX
- Flicker-free
- With a beam angle of 20° - 45°
- Very high color rendering index (CRI)
- With mounting bracket
- Mains input and output for power linking up to 8 units
- Built with SEETRONIC connector
- For application areas such as: Stage; Trade fair and shop fitting; wedding/gala/events; theater; rental; video and photography
- Application possibility: Suspended; on stand

### Logistic

EAN / GTIN: 4026397625714

Weight: 12,80 kg

Length: 0.80 m

Width: 0.32 m

Height: 0.33 m

### Technical specifications:

Power supply: 100-240 V AC, 50/60 Hz

Power consumption: 230 W

Protection class: Protection class I

|                              |                                                                                                 |
|------------------------------|-------------------------------------------------------------------------------------------------|
| Power connection:            | Mains input via P-Con (blue), mounting version<br>power supply cord with safety plug (provided) |
| Power output:                | 1 x P-Con (grey), mounting version                                                              |
| Lamp type:                   | LED lamp                                                                                        |
| LED type:                    | 1 x 200 W COB (chip-on-board) warm white<br>(WW)                                                |
| Equipment:                   | Focus manual; zoom manual                                                                       |
| Gobos:                       | Outside diameter 85mm<br>Image diameter 60mm                                                    |
| DMX channels:                | 1; 2                                                                                            |
| DMX input:                   | 1 x 5-pin XLR (M) mounting version<br>1 x 3-pin XLR (M) mounting version                        |
| DMX output:                  | 1 x 5-pin XLR (F) mounting version<br>1 x 3-pin XLR (F) mounting version                        |
| Cooling:                     | Low-noise cooling fan                                                                           |
| Control:                     | DMX                                                                                             |
| Fixtures available for:      | LED PC-Control 512; Light Captain                                                               |
| Projection:                  | Flicker-free                                                                                    |
| Beam angle:                  | 20° - 45°                                                                                       |
| Beam angle (1/2 peak):       | 20 - 45°                                                                                        |
| Beam angle (1/10 peak):      | 20 - 45°                                                                                        |
| Color rendering index (CRI): | 97 Ra                                                                                           |
| Housing color:               | Black                                                                                           |
| Attachment system:           | Mounting bracket                                                                                |
| Use of brands:               | Built with SEETRONIC connector                                                                  |
| Dimensions:                  | Length: 64.5 cm<br>Width: 27.6 cm<br>Height: 27.7 cm                                            |
| Weight:                      | 10.90 kg                                                                                        |
| Noise classification:        | Class 2 (slight noise)                                                                          |

## Scope of delivery:

1 x spotlight  
 1 x user manual  
 1 x power cord  
 1 x filter frame  
 1 x holder  
 1 x XLR cable  
 1 x plug (male)