

FUTURELIGHT EYE-740 MK2 QCL Zoom LED Moving Head Wash

PRO Washlight with 40 W Osram Ostar RGBW LEDs, large zoom range and pixel control

Art. No.: 51841303

GTIN: 4026397715613



List price: on demand €

incl. 19% VAT.

Features:

- Compact lightweight
- Crossfade channel from any color to white
- Number of scenes can be changed individually
- 7 LEDs 40 W 4in1 RGBW (homogenous color mix) LEDs controlled separately
- OSRAM LED installed
- Positioning within 540° PAN, 210° TILT
- Auto position correction (feedback)
- Exact positioning (16 bit resolution)
- Exact 16 bit resolution at Dimmer, color, zoom
- Zoom motor driven
- Patterns animated; dimmer curves with adjustable response; pulse-width modulation variable; pulse effect adjustable; white balance; scenes user-definable; CTO correction filter virtual; Dim to warm; colors preset; Dimmer speed (step response) adjustable
- Strobe effect
- Can be operated in 18; 25; 37; 26; 33; 45; 46; 53; 65 CH mode
- The device is cooled by temperature-controlled fan
- Control via stand-alone; master/slave function; DMX; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional); CRMX by LumenRadio upgradeable; RDM; sound to light via microphone
- Flicker-free
- With a beam angle of 1° - 48°
- Variable color temperature 2800 K - 10000 K
- With omega bracket
- Multicolor LCD display, with battery buffering for easy controlling upgradeable
- Rubber feet
- Mains input and output for power linking up to 8 units

Logistic

EAN / GTIN: 4026397715613

Weight: 9,35 kg

Length: 0.44 m

Width: 0.33 m

Height: 0.33 m

- For application areas such as: Wedding/gala/events; stage; theater; rental; video and photography
- Very quiet working noise
- Application possibility: Standing; suspended

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	210 W
Protection class:	Protection class I
Power connection:	Mains input via IP T-Con (M) mounting version power supply cord with safety plug
Power output:	IP T-Con (F) mounting version
Fuse:	5 x 20 mm, T 2 A fuse replaceable
Lamp type:	LED lamp
LED type:	7 x 40 W 4in1 RGBW (homogenous color mix)
LED manufacturer:	OSRAM
Max. TILT movement:	210° exact positioning (16 bit resolution) auto position correction (feedback)
Max. PAN movement:	540° exact positioning (16 bit resolution) auto position correction (feedback)
Flash rate:	0.5 - 16 Hz
Equipment:	Zoom motor driven
DMX channels:	18; 25; 37; 26; 33; 45; 46; 53; 65
DMX input:	3-pin XLR (M) mounting version 5-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version 5-pin XLR (F) mounting version
Cooling:	Temperature-controlled fan
Control:	Stand-alone; master/slave function; DMX; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional); CRMX by LumenRadio upgradeable; RDM; sound to light via microphone
Fixtures available for:	Light Captain; GDTF (GrandMA3)
Projection:	Flicker-free
Beam angle:	1° - 48°
Beam angle (1/2 peak):	1 - 32°
Beam angle (1/10 peak):	5 - 48°
Color temperature:	2800K - 10000K adjustable
Illuminance in Lux (lx):	Narrow red (R) 3m: 6818 lx, 6m: 1758 lx Narrow green (G) 3m: 12807 lx, 6m: 3122 lx Narrow blue (B) 3m: 2513 lx, 6m: 21580 lx Narrow cold white (CW) 3m: 21580 lx, 6m: 5431 lx Narrow all 3m: 38576 lx, 6m: 9662 lx Wide red (R) 3m: 162 lx, 6m: 46 lx Wide green (G) 3m: 315 lx, 6m: 89 lx Wide blue (B) 3m: 85 lx, 6m: 25 lx Wide cold white (CW) 3m: 504 lx, 6m: 143 lx

	Wide all 3m: 915 lx, 6m: 259 lx
Housing color:	Black
Attachment system:	Omega bracket
Display type:	Multicolor LCD display battery buffering upgradeable
Transport aid:	Rubber feet
Dimensions:	Width: 28.6 cm Depth: 24.5 cm Height: 37.2 cm
Weight:	8.10 kg
Noise classification:	Class 1 (very slight noise, suitable for noise-sensitive environments)

Scope of delivery:

1 x moving light
 1 x user manual
 1 x power cord
 1 x omega bracket
 1 x XLR cable