

## FUTURELIGHT EYE-7 RGBW Zoom LED Moving Head Wash

PRO washlight, compact with RGBW color mixing and very large zoom range

Art. No.: 51841308

GTIN: 4026397545432



### Features:

- Equipped with 7 x 15 W quadcolor LED with RGBW colors (Osram)
- Upgrade via optional wireless receiver module for WDMX operation (Wireless Solution - made in Sweden)
- Compact housing
- High PAN/TILT speed
- Exact positioning via 16 bit PAN/TILT movement resolution
- Master dimmer
- Motorized zoom with 2 - 41° beam angle
- Each color of the 7 RGBW LEDs can be switched individually
- Color presets
- Preset color temperatures
- Built-in programs
- Animated and static macros
- Stepless RGBW color mixture
- Strobe effect with adjustable speed
- Random strobe effect
- Automatic position correction
- PAN angle switchable between 540° and 630°
- ESDC function (Easy Service Data Check) with battery-buffered control board for operation time readouts etc. (the Li-Ion battery 3.7V, AAA, 10440 is not included)
- Switch-mode power supply, automatic power supply adaption between 100 and 240 Volts without power selector
- Control board with graphic LCD and foil-keyboard for adjusting the DMX-starting address, PAN/TILT reverse, reset
- DMX-controlled operation or stand-alone operation with Master/Slave function

### Logistic

EAN / GTIN: 4026397545432

Weight: 8,10 kg

Length: 0.46 m

Width: 0.32 m

Height: 0.27 m

- The scenes can be modified via the Control Board or via an external controller and loaded into the memory
- Number of scenes can be changed individually
- Software upload by optional accessories via DMX link
- Power connection via Neutrik PowerCon jack and included power cable
- Feed-through output allows to power another device
- After every 8 device the fixtures must have a renewed connection with the power mains
- DMX control via every standard DMX controller
- 7 LEDs 15 W high-power 4in1 RGBW (homogenous color mix)
- PAN angle switchable between 540° and 630°
- Auto position correction (feedback)
- Exact positioning (16 bit resolution)
- Zoom motor driven
- Beam effect
- Can be operated in 18; 19; 20; 50 CH mode
- The device is cooled by temperature-controlled fan
- Control via RDM; DMX; stand-alone; W-DMX by wireless solution upgradeable; sound to light via microphone
- Flicker-free
- With a beam angle of 2° - 41°

## Technical specifications:

|                          |                                                                                                                                                                                |
|--------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Power supply:            | 100-240 V AC, 50/60 Hz                                                                                                                                                         |
| Power consumption:       | 110 W                                                                                                                                                                          |
| Power connection:        | Mains input via PowerCON (blue), mounting version power supply cord with safety plug (provided)                                                                                |
| Power output:            | 1 x PowerCON (grey), mounting version                                                                                                                                          |
| Lamp type:               | LED lamp                                                                                                                                                                       |
| LED type:                | 7 x 15 W high-power 4in1 RGBW (homogenous color mix)                                                                                                                           |
| Max. TILT movement:      | 270° exact positioning (16 bit resolution) auto position correction (feedback)                                                                                                 |
| Max. PAN movement:       | 540°, 630° exact positioning (16 bit resolution) auto position correction (feedback)                                                                                           |
| Flash rate:              | 0 - 18 Hz                                                                                                                                                                      |
| Equipment:               | Zoom motor driven                                                                                                                                                              |
| DMX channels:            | 18; 19; 20; 50                                                                                                                                                                 |
| DMX input:               | 1 x 5-pin XLR (M) mounting version                                                                                                                                             |
| DMX output:              | 1 x 5-pin XLR (F) mounting version                                                                                                                                             |
| Cooling:                 | Temperature-controlled fan                                                                                                                                                     |
| Control:                 | RDM; DMX; stand-alone; W-DMX by wireless solution upgradeable; sound to light via microphone                                                                                   |
| Fixtures available for:  | LED PC-Control 512                                                                                                                                                             |
| Projection:              | Flicker-free                                                                                                                                                                   |
| Beam angle:              | 2° - 41°                                                                                                                                                                       |
| Beam angle (1/2 peak):   | 2 - 23°                                                                                                                                                                        |
| Beam angle (1/10 peak):  | 6 - 41°                                                                                                                                                                        |
| Illuminance in Lux (lx): | Narrow red (R) 3m: 1197 lx, 6m: 329 lx<br>Narrow green (G) 3m: 3225 lx, 6m: 824 lx<br>Narrow blue (B) 3m: 560 lx, 6m: 144 lx<br>Narrow cold white (CW) 3m: 3792 lx, 6m: 976 lx |

Narrow all 3m: 7966 lx, 6m: 2056 lx  
Wide red (R) 3m: 82 lx, 6m: 23 lx  
Wide green (G) 3m: 230 lx, 6m: 61 lx  
Wide blue (B) 3m: 40 lx, 6m: 11 lx  
Wide cold white (CW) 3m: 266 lx, 6m: 72 lx  
Wide all 3m: 559 lx, 6m: 151 lx

|                |                                                     |
|----------------|-----------------------------------------------------|
| Housing color: | Black                                               |
| Dimensions:    | Width: 24.9 cm<br>Depth: 17.9 cm<br>Height: 34.7 cm |
| Weight:        | 6.00 kg                                             |

**Scope of delivery:**

- 1 x moving light
- 1 x user manual
- 1 x power cord
- 1 x omega bracket
- 1 x XLR cable