

## FUTURELIGHT Stage Pixel Bar 5

Bar with narrow beam 5 x 15 W RGBW LED and frost plate

Art. No.: 51841358

GTIN: 4026397561081



**The article is no longer in our assortment.**

### Features:

- Additional frost filter provides a wide, soft and homogeneous light
- For use via appropriate lighting control software supporting Art-Net
- 5 LEDs 15 W high-power 4in1 RGBW (homogenous color mix) LEDs controlled separately
- Color change adjustable; Dimmer speed (step response) adjustable
- Strobe effect
- Integrated show programs
- Direct color selection
- Can be operated in 4; 6; 8; 20; 24 CH mode
- Control via Art-Net; stand-alone; DMX; sound to light via microphone; RDM
- Flicker-free
- With a beam angle of 4°
- With mounting bracket
- Mains input and output for power linking up to 8 units
- For application areas such as: Clubs/dancing school; stage; rental
- Application possibility: Standing; suspended; on stand

### Logistic

EAN / GTIN: 4026397561081

Weight: 7,20 kg

Length: 0.54 m

Width: 0.27 m

Height: 0.23 m

### Technical specifications:

|                    |                                                                                                 |
|--------------------|-------------------------------------------------------------------------------------------------|
| Power supply:      | 100-240 V AC, 50/60 Hz                                                                          |
| Power consumption: | 100 W                                                                                           |
| Power connection:  | Mains input via PowerCON (blue), mounting version power supply cord with safety plug (provided) |

|                         |                                                                          |
|-------------------------|--------------------------------------------------------------------------|
| Power output:           | 1 x PowerCON (grey), mounting version                                    |
| Lamp type:              | LED lamp                                                                 |
| LED type:               | 5 x 15 W high-power 4in1 RGBW (homogenous color mix)                     |
| Flash rate:             | 0 - 18 Hz                                                                |
| DMX channels:           | 4; 6; 8; 20; 24                                                          |
| DMX input:              | 1 x 3-pin XLR (M) mounting version<br>1 x 5-pin XLR (M) mounting version |
| DMX output:             | 1 x 3-pin XLR (F) mounting version<br>1 x 5-pin XLR (F) mounting version |
| Network connection:     | Protocol: Art-Net 3 via 2x RJ-45 etherCON (F) mounting version           |
| Control:                | Art-Net; stand-alone; DMX; sound to light via microphone; RDM            |
| Fixtures available for: | Light J; Light Captain; EASY SHOW 1; EASY SHOW 2; EASY SHOW 3            |
| Projection:             | Flicker-free                                                             |
| Beam angle:             | 4°                                                                       |
| Beam angle (1/2 peak):  | 4°                                                                       |
| Beam angle (1/10 peak): | 7°                                                                       |
| Housing color:          | Black                                                                    |
| Attachment system:      | Mounting bracket                                                         |
| Dimensions:             | Length: 44 cm<br>Depth: 16 cm<br>Height: 17.3 cm                         |
| Weight:                 | 6.15 kg                                                                  |

### Scope of delivery: