

FUTURELIGHT Stage Pixel Bar 5

Bar with narrow beam 5 x 15 W RGBW LED and frost plate

Art. No.: 51841358

GTIN: 4026397561081



Features:

- Additional frost filter provides a wide, soft and homogeneous light
- For use via appropriate lighting control software supporting Art-Net
- 5 LEDs 15 W high-power 4in1 RGBW (homogenous color mix) LEDs controlled separately
- Color change adjustable; Dimmer speed (step response) adjustable
- Strobe effect
- Integrated show programs
- Direct color selection
- Can be operated in 4; 6; 8; 20; 24 CH mode
- Control via Art-Net; stand-alone; DMX; sound to light via microphone; RDM
- Flicker-free
- With a beam angle of 4°
- With mounting bracket
- Mains input and output for power linking up to 8 units
- For application areas such as: Clubs/dancing school; stage; rental
- Application possibility: Standing; suspended; on stand

Logistic

EAN / GTIN: 4026397561081

Weight: 7,20 kg

Length: 0.54 m

Width: 0.27 m

Height: 0.23 m

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	100 W
Power connection:	Mains input via PowerCON (blue), mounting version power supply cord with safety plug (provided)

Power output:	1 x PowerCON (grey), mounting version
Lamp type:	LED lamp
LED type:	5 x 15 W high-power 4in1 RGBW (homogenous color mix)
Flash rate:	0 - 18 Hz
DMX channels:	4; 6; 8; 20; 24
DMX input:	1 x 3-pin XLR (M) mounting version 1 x 5-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version 1 x 5-pin XLR (F) mounting version
Network connection:	Protocol: Art-Net 3 via 2x RJ-45 etherCON (F) mounting version
Control:	Art-Net; stand-alone; DMX; sound to light via microphone; RDM
Fixtures available for:	Light J; Light Captain; EASY SHOW 1; EASY SHOW 2; EASY SHOW 3
Projection:	Flicker-free
Beam angle:	4°
Beam angle (1/2 peak):	4°
Beam angle (1/10 peak):	7°
Housing color:	Black
Attachment system:	Mounting bracket
Dimensions:	Length: 44 cm Depth: 16 cm Height: 17.3 cm
Weight:	6.15 kg

Scope of delivery: