

FUTURELIGHT Stage Pixel Bar 10

Bar with narrow beam 10 x 15 W RGBW LED and frost plate

Art. No.: 51841359

GTIN: 4026397561098



The article is no longer in our assortment.

Features:

- Equipped with 10 high-power 4in1 LEDs in the colors red, green, blue and white
- Particularly bright illuminating power of the LEDs
- Collimator lenses for homogeneous beams with 4° beam angle
- Removable frost filter
- 4, 6, 8, 40 or 44 DMX channels selectable
- Each LED can be controlled individually
- Quick and easy control via Art-Net
- For use via appropriate lighting control software supporting Art-Net
- Programmable color change speed, strobe effect and dimmer
- Dimmer speed (step response) adjustable
- Strobe effect with 1-18 flashes per second
- RGBW color mixing
- Static colors
- Internal programs
- DMX-controlled operation or stand-alone operation with Master/Slave function
- Manual, sound, DMX- or ArtNet-controlled operation
- Sound-control via built-in microphone; adjustable sensitivity
- For large stage backgrounds in public places, main halls and lounges
- Hanging as well as standing installation possible
- Locking possibility at the mounting bracket
- Addressing via control panel with LCD screen and four operating buttons
- EtherCon input and output
- Switch-mode power supply for operation between 100 and 240 volts
- Power connection via Neutrik PowerCon jack and included power cable with safety plug
- Feed-through output allows to power up to 8 devices
- DMX control via any standard DMX controller

Logistic

EAN / GTIN: 4026397561098

Weight: 11,60 kg

Length: 0.97 m

Width: 0.24 m

Height: 0.27 m

- 10 LEDs 15 W high-power 4in1 RGBW (homogenous color mix)
- Strobe effect
- Can be operated in 4; 6; 8; 40; 44 CH mode
- Control via Art-Net; stand-alone; DMX; sound to light via microphone; RDM
- Flicker-free
- With a beam angle of 4°

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	170 W
Power connection:	Mains input via PowerCON (blue), mounting version power supply cord with safety plug (provided)
Power output:	1 x PowerCON (grey), mounting version
Lamp type:	LED lamp
LED type:	10 x 15 W high-power 4in1 RGBW (homogenous color mix)
Flash rate:	0 - 18 Hz
DMX channels:	4; 6; 8; 40; 44
Control:	Art-Net; stand-alone; DMX; sound to light via microphone; RDM
Fixtures available for:	Light J; LED PC-Control 512; EASY SHOW 1
Projection:	Flicker-free
Beam angle:	4°
Beam angle (1/2 peak):	4°
Beam angle (1/10 peak):	7°
Housing color:	Black
Dimensions:	Length: 88 cm Depth: 15.9 cm Height: 17.8 cm
Weight:	9.70 kg
Protocol:	Art-Net 3
Signal port:	2 x RJ45 (EtherCon)
DMX connection:	5-pin and 3-pin XLR

Scope of delivery: