FUTURELIGHT DMH-40 LED Moving Head

High performance LED moving head

Art. No.: 51841835

GTIN: 4026397420708











The article is no longer in our assortment.

Features:

- 1 extra bright 40 W LED for best luminance
- Comparable to the light output of 250 W discharge lamp
- Effect wheel with rotating 3-facet prism and 3D prism and frost filter
- Macro function for rotating gobos/rotating prism combinations
- Color wheel with 8 different dichroic color filters plus white
- Switchable color change (mode 1: only full colors, mode 2: color change at every position)
- Rainbow effect with adjustable speed in both directions
- Gobo wheel with 7 rotating gobos plus open
- All gobos can be interchanged
- Slot-in gobo system for exchanging gobos without tools
- With gobo shake function
- Exact positioning via 16 bit PAN/TILT movement resolution
- Motorized focus
- Dimmer
- Strobe effect with adjustable speed
- Random strobe effect
- Power standby mode
- PAN angle switchable between 630° and 540°
- Switch-mode power supply, automatic power supply adaption between 100 and 240 Volts without power selector
- Control board with 4-digit display and foil-keyboard for adjusting the DMX starting address, PAN/TILT Reverse, Program, Reset
- DMX-controlled operation or stand-alone operation with Master/Slave function
- 56 preprogrammed scenes in Program Run for stand-alone operation
- Number of scenes in Program Run can be changed individually

Logistic

EAN / GTIN: 4026397420708
Weight: 12,70 kg
Length: 0.47 m
Width: 0.34 m
Heigth: 0.39 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

- The scenes in Program Run can be modified via the Control Board or via an external controller and loaded into the memory
- 7 built-in programs can be called up via DMX controller
- Software upload by optional FUTURELIGHT ULB-1 upload box via DMX link
- Sound-controlled via built-in microphone
- DMX control via every standard DMX controller
- Can be operated in 14 CH mode
- Control via sound to light via microphone; DMX; RDM

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	150 W
Flash rate:	1 - 22 Hz
Gobos:	Outside diameter 27mm Image diameter 22mm
DMX channels:	14
Control:	Sound to light via microphone; DMX; RDM
Beam angle (1/2 peak):	15°
Color:	Black
Dimensions:	Length: 30.10 cm
Weight:	11.30 kg
DMX channels:	14
DMX connection:	5-pin and 3-pin XLR
Sound-control:	via built-in microphone
Flash-rate:	22 Hz
LED type:	LUMINUS SST-90
LED number:	1
Beam angle:	15°
Color-wheel:	8 dichroic filters plus open
Rotating gobo-wheel:	7 gobos and open
Outside diameter of the gobos:	27 mm
Image diameter of the gobos:	22 mm
Length of base:	301 mm
Width of yoke:	247 mm
Height (head horizontal):	406 mm

Scope of delivery:

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.