

FUTURELIGHT PRO Slim PAR-7 Hypno HCL

Flat PRO spotlight with RGBWA+UV LEDs (6in1) and RGB SMD ring

Art. No.: 51842548

GTIN: 4026397614626



The article is no longer in our assortment.

Features:

- Equipped with 7 high-power RGBWA+UV-LEDs (6in1) and 144 RGB LEDs (SMD)
- Individually controllable segments
- Flat version requires minimal space when mounting
- Compact design
- Additional bracket for floor use
- 2 swivel mounting brackets
- Control panel with LED display for easy configuration
- Stand-alone or DMX mode
- Mains input and output for power linking up to 8 units
- 144 LEDs SMD 5050 3in1 RGB (homogenous color mix)
- 7 LEDs 8 W high-power 6in1 RGBWA/UV (homogenous color mix)
- Strobe effect; UV effect
- Can be operated in 11; 16; 28 CH mode
- The device is cooled by passive convection cooling
- Control via DMX; sound to light via microphone
- Flicker-free
- With a beam angle of 20°
- Silent operation

Logistic

EAN / GTIN: 4026397614626

Weight: 5,50 kg

Length: 0.25 m

Width: 0.25 m

Height: 0.31 m

Technical specifications:

Power supply: 100-240 V AC, 50/60 Hz

Power consumption: 80 W

Protection class: Protection class I

Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Power output:	1 x P-Con (grey), mounting version
Lamp type:	LED lamp
LED type:	144 x SMD 5050 3in1 RGB (homogenous color mix) 7 x 8 W high-power 6in1 RGBWA/UV (homogenous color mix)
DMX channels:	11; 16; 28
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Passive convection cooling
Control:	DMX; sound to light via microphone
Fixtures available for:	LED PC-Control 512; Light Captain
Projection:	Flicker-free
Beam angle:	20°
Beam angle (1/2 peak):	20°
Beam angle (1/10 peak):	34°
Housing color:	Black
Dimensions:	Width: 28.7 cm Depth: 12.6 cm Height: 30 cm
Weight:	5 kg
Noise classification:	Class 0 (no noise at all)

Scope of delivery: