

FUTURELIGHT PRO Slim PAR-12 MK2 TCL

Flat PRO LED spotlight with 12 x 9 W 3in1 LED (RGB) without fan

Art. No.: 51842562

GTIN: 4026397614015



The article is no longer in our assortment.

Description:

Flat, professional LED spot without fan

The FUTURELIGHT PRO Slim PAR-12 MK2 TCL is equipped with 12 powerful 3in1 tricolor LEDs in red, green and blue. The slim spot is suitable for use on larger stages and in discotheques. Thanks to the pure convection cooling, you can also use it in theatres or at galas, because it is noiseless in operation. Due to the compact and flat housing, you only need minimal space during installation.

The LEDs with RGB color mixing produce rich and homogeneous colors. The flicker-free Slim Spot is dimmable and has strobe settings with variable speed.

Several devices can be synchronised in master/slave mode. Powercon mains connections are located at the rear of the unit, allowing up to eight units to be operated in series. The LED spot can be controlled via DMX or in stand-alone mode.

Features:

- Equipped with 12 x 3in1 tricolor LEDs in the colors red, green and blue
- Flat housing form requires minimal space when rigging
- Extremely compact housing in a beautiful design
- Second mounting bracket for safe standing installation
- Locking possibility at the brackets with large metal butterfly screws
- Functions: static colors, RGB color mixture, automatic color changes, dimmer, strobe effect with adjustable speed, Master/Slave operation
- Microphone-sensitivity adjustable via Control Board
- Addressing and setting via Control Board with four operating buttons and LED display
- Operable in stand-alone mode or via DMX

Logistic

EAN / GTIN: 4026397614015

Weight: 5,50 kg

Length: 0.25 m

Width: 0.25 m

Height: 0.30 m

- Switch-mode power supply for operation between 100 and 240 volts
- P-Con terminals for power linking up to 8 units
- 12 LEDs 9 W high-power 3in1 RGB (homogenous color mix)
- Strobe effect
- Can be operated in 3; 5; 7 CH mode
- The device is cooled by passive convection cooling
- Control via stand-alone; DMX; sound to light via microphone
- Flicker-free
- With a beam angle of 9°
- Silent operation

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	85 W
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Power output:	1 x P-Con (grey), mounting version
Lamp type:	LED lamp
LED type:	12 x 9 W high-power 3in1 RGB (homogenous color mix)
DMX channels:	3; 5; 7
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Passive convection cooling
Control:	Stand-alone; DMX; sound to light via microphone
Fixtures available for:	Light´J; LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain
Projection:	Flicker-free
Beam angle:	9°
Beam angle (1/2 peak):	9°
Beam angle (1/10 peak):	20°
Housing color:	Black
Dimensions:	Width: 28.7 cm Depth: 12.6 cm Height: 30 cm
Weight:	5.00 kg
Noise classification:	Class 0 (no noise at all)

Scope of delivery:

- 1 x spotlight
- 1 x user manual
- 1 x power cord