

FUTURELIGHT PRO Slim PAR-12 MK2 CW/WW/A

Flat PRO white light spotlight with 3in1 LEDs in cold white, warm white and amber

Art. No.: 51842563

GTIN: 4026397628210



The article is no longer in our assortment.

Features:

- Flat version requires minimal space when mounting
- Compact design
- Fuzzy sound control: program continues automatically during periods without music or bass-beat
- 12 LEDs 5 W high-power 3in1 CW/WW/A (homogenous color mix)
- Color change adjustable; Dimmer electronic; color blend stepless
- Strobe effect
- Can be operated in 3; 5; 7 CH mode
- The device is cooled by passive convection cooling
- Control via stand-alone; DMX; sound to light via microphone; master/slave function
- Flicker-free
- With a beam angle of 11°
- Variable color temperature 2700 K - 6100 K
- With double bracket
- Mains input and output for power linking up to 8 units
- Silent operation

Logistic

EAN / GTIN: 4026397628210

Weight: 5,45 kg

Length: 0.26 m

Width: 0.26 m

Height: 0.31 m

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	80 W
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)

Power output:	1 x P-Con (grey), mounting version
Lamp type:	LED lamp
LED type:	12 x 5 W high-power 3in1 CW/WW/A (homogenous color mix)
DMX channels:	3; 5; 7
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Passive convection cooling
Control:	Stand-alone; DMX; sound to light via microphone; master/slave function
Fixtures available for:	LED PC-Control 512; Light Captain; Light´J
Projection:	Flicker-free
Beam angle:	11°
Beam angle (1/2 peak):	11°
Beam angle (1/10 peak):	23°
Color temperature:	2700K - 6100K adjustable
Housing color:	Black
Attachment system:	Double bracket
Dimensions:	Width: 28.7 cm Depth: 12.6 cm Height: 30 cm
Weight:	5 kg
Noise classification:	Class 0 (no noise at all)

Scope of delivery: