

FUTURELIGHT PRO Slim PAR-6 COB RGB

PRO slimline LED spot with 6 x 30 W COB (RGB) without fan

Art. No.: 51842564

GTIN: 4026397651577



The article is no longer in our assortment.

Features:

- 6 high-power 30 W COB LEDs (3in1)
- Flat version requires minimal space when mounting
- Compact design
- Additional bracket for floor use
- Stepless color blend, color change, preset colors, dimmer and strobe effect
- Fuzzy sound control: program continues automatically during periods without music or bass-beat
- Control panel with LED display for easy configuration
- Mains input and output for power linking up to 8 units
- 6 LEDs 30 W COB (chip-on-board) 3in1 RGB (homogenous color mix)
- Strobe effect
- Can be operated in 3; 5; 7 CH mode
- The device is cooled by passive convection cooling
- Control via DMX; sound to light via microphone; master/slave function
- Flicker-free
- With a beam angle of 36°
- With mounting bracket
- Silent operation

Logistic

EAN / GTIN: 4026397651577

Weight: 5,50 kg

Length: 0.26 m

Width: 0.26 m

Height: 0.31 m

Technical specifications:

Power supply: 100-240 V AC, 50/60 Hz

Power consumption: 115 W

Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug
Lamp type:	LED lamp
LED type:	6 x 30 W COB (chip-on-board) 3in1 RGB (homogenous color mix)
DMX channels:	3; 5; 7
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Passive convection cooling
Control:	DMX; sound to light via microphone; master/slave function
Fixtures available for:	Light J; LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain
Projection:	Flicker-free
Beam angle:	36°
Beam angle (1/2 peak):	36°
Beam angle (1/10 peak):	80°
Housing color:	Black
Attachment system:	2x mounting bracket
Dimensions:	Width: 28.7 cm Depth: 12.6 cm Height: 30 cm
Weight:	5.07 kg
Noise classification:	Class 0 (no noise at all)

Scope of delivery:

1 x spotlight
1 x user manual
1 x power cord