

FUTURELIGHT PRO Slim Strobe SMD 840 CW

Art. No.: 51842710

PRO slimline LED strobe with 840 x cold white (CW) LEDs, 16 separately controllable LED rings and switchable frost



List price: 236.81 €

incl. 19% VAT.

Features:

- 840 LEDs 0.5 W SMD 5730 cold white (CW)
16 segments controlled separately
- Frost filter electronic
- Strobe effect
- 27 integrated show programs
- Can be operated in 2; 3; 5; 7; 17; 23 CH mode
- The device is cooled by passive convection cooling
- Control via stand-alone; master/slave function; DMX; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
- Flicker-free
- With mounting bracket
- LCD display
- Mains input and output for power linking up to 8 units
- For application areas such as: Clubs/dancing school; stage; theater; rental; wedding/gala/events; mobile djs / entertainer
- Silent operation
- Application possibility: Suspended; on stand

Logistic

EAN / GTIN: 4026397716368

Weight: 6,15 kg

Length: 0.30 m

Width: 0.30 m

Height: 0.30 m

Technical specifications:

Power supply: 100-240 V AC, 50/60 Hz

Power consumption: 150 W

Protection class: Protection class I

Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug
Power output:	P-Con (grey), mounting version
Lamp type:	LED lamp
LED type:	840 x 0.5 W SMD 5730 cold white (CW)
Flash rate:	1 - 30 Hz
DMX channels:	2; 3; 5; 7; 17; 23
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	Passive convection cooling
Control:	Stand-alone; master/slave function; DMX; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
Fixtures available for:	Light Captain
Projection:	Flicker-free
Color temperature:	6300K
Attachment system:	Mounting bracket
Display type:	LCD display
Dimensions:	Width: 30.5 cm Depth: 14.5 cm Height: 34.5 cm
Weight:	5.50 kg
Noise classification:	Class 0 (no noise at all)

Scope of delivery:

1 x light effect
1 x user manual
1 x power cord