

EUROLITE LED FLD-1508 UV Panel

Extremely bright UV spot with 15 x 8 W LED, incl. IR remote control

Art. No.: 51913863

GTIN: 4026397654707



The article is no longer in our assortment.

Features:

- Brightness and flash rate steplessly adjustable
- Mains input and output for power linking up to 8 units
- 15 LEDs 8 W high-power ultra violet (UV)
- UV effect; strobe effect
- Integrated show programs
- Can be operated in 1; 4 CH mode
- The device is cooled by cooling fan
- Control via stand-alone; DMX; sound to light via microphone; master/slave function; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional); IR remote control
- With a beam angle of 14°
- With double bracket

Logistic

EAN / GTIN: 4026397654707

Weight: 3,84 kg

Length: 0.32 m

Width: 0.14 m

Height: 0.27 m

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	60 W
Protection class:	Protection class I
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Power output:	P-Con (grey), mounting version
Lamp type:	LED lamp

LED type:	15 x 8 W high-power ultra violet (UV)
DMX channels:	1; 4
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	Cooling fan
Control:	Stand-alone; DMX; sound to light via microphone; master/slave function; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional); IR remote control
Fixtures available for:	Light´J; LED PC-Control 512; Light Captain
Beam angle:	14°
Beam angle (1/2 peak):	14°
Beam angle (1/10 peak):	32°
Wavelength:	400 nm
Housing color:	Black
Attachment system:	Double bracket
Dimensions:	Width: 29.5 cm Depth: 11 cm Height: 22.8 cm
Weight:	3.60 kg
Photobiological safety:	Risk Group 0

Scope of delivery:

1 x user manual
1 x battery