

EUROLITE Stage Panel 16 HCL LED

Light effect bar with RGBAW+UV color mixing, with 5-pin QuickDMX connector

Art. No.: 51913891

GTIN: 4026397622522



List price: 391.51 €

incl. 19% VAT.

Features:

- 4 segments for dynamic running lights
- 4 barn doors to avoid blinding the audience and for protection during transport
- Improved version with more than predecessor model
- 16 LEDs 12 W high-power 6in1 RGBWA/UV (homogenous color mix)
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic
- Strobe effect; UV effect
- Integrated show programs
- Direct color selection for 26 preset colors
- Can be operated in 2; 3; 5; 6; 8; 11; 24; 32 CH mode
- The device is cooled by passive convection cooling
- Control via stand-alone; DMX; IR remote control; sound to light via microphone; QuickDMX via 5-pin XLR (M) mounting version (optional); master/slave function
- Flicker-free
- With a beam angle of 23°
- With mounting bracket
- Mains input and output for power linking up to 8 units
- Suitable for a range of use from to meters

Logistic

EAN / GTIN: 4026397622522

Weight: 5,80 kg

Length: 0.56 m

Width: 0.16 m

Heigh: 0.24 m

Technical specifications:

Power supply: 100-240 V AC, 50/60 Hz

Power consumption: 70 W

Protection class: Protection class I

Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Power output:	1 x P-Con (grey), mounting version
Fuse:	T 1 A fuse replaceable
Lamp type:	LED lamp
LED type:	16 x 12 W high-power 6in1 RGBWA/UV (homogenous color mix)
Flash rate:	0.25 - 16 Hz
DMX channels:	2; 3; 5; 6; 8; 11; 24; 32
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Passive convection cooling
Control:	Stand-alone; DMX; IR remote control; sound to light via microphone; QuickDMX via 5-pin XLR (M) mounting version (optional); master/slave function
Projection:	Flicker-free
PWM frequency:	4700 Hz
Beam angle:	23°
Beam angle (1/2 peak):	23°
Beam angle (1/10 peak):	42°
Color temperature:	7200K
Housing color:	Black
Attachment system:	Mounting bracket
Material:	Metal, painted; aluminum casting
Dimensions:	Width: 59.1 cm Depth: 19.9 cm Height: 30.3 cm
Weight:	5.35 kg
Photobiological safety:	Risk Group 0
Diameter mounting holes:	3 x Ø11mm; 4 x Ø10mm
Material:	Metal
Cable construction:	3 x 1.0 mm² H05VV-F
Cable length:	Approx. 1.2 m
Material:	Metal
Battery:	1 x button cell 3.0 V CR2025 lithium manganese built-in

Scope of delivery:

1 x spotlight
 1 x power cord
 1 x barndoor
 1 x remote control
 1 x battery
 1 x user manual