

## EUROLITE Stage Panel 16 HCL LED

Light effect bar with RGBAW+UV color mixing, with 5-pin QuickDMX connector

Art. No.: 51913891

GTIN: 4026397622522



### Features:

- 4 segments for dynamic running lights
- 4 barn doors to avoid blinding the audience and for protection during transport
- Improved version with more than predecessor model
- 16 LEDs 12 W high-power 6in1 RGBWA/UV (homogenous color mix)
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic
- Strobe effect; UV effect
- Integrated show programs
- Direct color selection for 26 preset colors
- Can be operated in 2; 3; 5; 6; 8; 11; 24; 32 CH mode
- The device is cooled by passive convection cooling
- Control via stand-alone; DMX; IR remote control; sound to light via microphone; QuickDMX via 5-pin XLR (M) mounting version (optional); master/slave function
- Flicker-free
- With a beam angle of 23°
- With mounting bracket
- Mains input and output for power linking up to 8 units
- Suitable for a range of use from to meters

### Logistic

EAN / GTIN: 4026397622522

Weight: 5,80 kg

Length: 0.56 m

Width: 0.16 m

Height: 0.24 m

### Technical specifications:

Power supply: 100-240 V AC, 50/60 Hz

Power consumption: 70 W

Protection class: Protection class I

|                          |                                                                                                                                                   |
|--------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------|
| Power connection:        | Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)                                                      |
| Power output:            | 1 x P-Con (grey), mounting version                                                                                                                |
| Fuse:                    | T 1 A fuse replaceable                                                                                                                            |
| Lamp type:               | LED lamp                                                                                                                                          |
| LED type:                | 16 x 12 W high-power 6in1 RGBWA/UV (homogenous color mix)                                                                                         |
| Flash rate:              | 0.25 - 16 Hz                                                                                                                                      |
| DMX channels:            | 2; 3; 5; 6; 8; 11; 24; 32                                                                                                                         |
| DMX input:               | 1 x 3-pin XLR (M) mounting version                                                                                                                |
| DMX output:              | 1 x 3-pin XLR (F) mounting version                                                                                                                |
| Cooling:                 | Passive convection cooling                                                                                                                        |
| Control:                 | Stand-alone; DMX; IR remote control; sound to light via microphone; QuickDMX via 5-pin XLR (M) mounting version (optional); master/slave function |
| Projection:              | Flicker-free                                                                                                                                      |
| PWM frequency:           | 4700 Hz                                                                                                                                           |
| Beam angle:              | 23°                                                                                                                                               |
| Beam angle (1/2 peak):   | 23°                                                                                                                                               |
| Beam angle (1/10 peak):  | 42°                                                                                                                                               |
| Color temperature:       | 7200K                                                                                                                                             |
| Housing color:           | Black                                                                                                                                             |
| Attachment system:       | Mounting bracket                                                                                                                                  |
| Material:                | Metal, painted; aluminum casting                                                                                                                  |
| Dimensions:              | Width: 59.1 cm<br>Depth: 19.9 cm<br>Height: 30.3 cm                                                                                               |
| Weight:                  | 5.35 kg                                                                                                                                           |
| Photobiological safety:  | Risk Group 0                                                                                                                                      |
| Diameter mounting holes: | 3 x Ø11mm; 4 x Ø10mm                                                                                                                              |
| Material:                | Metal                                                                                                                                             |
| Cable construction:      | 3 x 1.0 mm² H05VV-F                                                                                                                               |
| Cable length:            | Approx. 1.2 m                                                                                                                                     |
| Material:                | Metal                                                                                                                                             |
| Battery:                 | 1 x button cell 3.0 V CR2025 lithium manganese built-in                                                                                           |

### Scope of delivery:

1 x spotlight  
 1 x power cord  
 1 x barndoor  
 1 x remote control  
 1 x battery  
 1 x user manual