

EUROLITE LED CLS-9 QCL RGB/WW 9x7W

LED floodlight with RGB/WW color mixing, barn doors, IR remote control and frost filter

Art. No.: 51913901

GTIN: 4026397712841



Features:

- Additional frost filter provides a wide, soft and homogeneous light
- 9 LEDs 7 W 4in1 RGB/WW (homogenous color mix)
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic; Dimmer speed (step response) adjustable; white balance
- Strobe effect
- Can be operated in 3; 4; 6; 8; 11 CH mode
- The device is cooled by passive convection cooling
- Control via stand-alone; DMX; QuickDMX (optional); W-DMX by wireless solution (optional); CRMX by LumenRadio (optional); master/slave function; sound to light via microphone; IR remote control
- Flicker-free
- With a beam angle of 10°
- With mounting bracket
- OLED display
- Mains input and output for power linking up to 8 units
- For application areas such as: Stage; clubs/dancing school; wedding/gala/events; mobile djs / entertainer; party room; restaurants, bars and hotels; theater
- Silent operation
- Application possibility: Standing; suspended; on stand
- 3 buttons on the remote control for saving your own settings

Logistic

EAN / GTIN: 4026397712841

Weight: 3,50 kg

Length: 0.30 m

Width: 0.19 m

Height: 0.24 m

Technical specifications:

Power supply: 100-240 V AC, 50/60 Hz

Power consumption:	54 W
Protection class:	Protection class I
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Power output:	1 x PowerCON (grey)
Lamp type:	LED lamp
LED type:	9 x 7 W 4in1 RGB/WW (homogenous color mix)
Flash rate:	1 - 23 Hz
DMX channels:	3; 4; 6; 8; 11
DMX input:	1 x 3-pin XLR (M) mounting version 1 x 5-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version 1 x 5-pin XLR (F) mounting version
Cooling:	Passive convection cooling
Control:	Stand-alone; DMX; QuickDMX (optional); W-DMX by wireless solution (optional); CRMX by LumenRadio (optional); master/slave function; sound to light via microphone; IR remote control
Fixtures available for:	Light Captain; EASY SHOW 2; EASY SHOW 3; Colorchief
Projection:	Flicker-free
Beam angle:	10°
Beam angle (1/2 peak):	10° Frost filter 18°
Beam angle (1/10 peak):	28° Frost filter 47°
Housing color:	Black
Attachment system:	Mounting bracket
Display type:	OLED display
Dimensions:	Length: 27.1 cm Width: 14.3 cm Height: 21.3 cm
Weight:	3.20 kg
Noise classification:	Class 0 (no noise at all)
Battery:	1 x button cell 3.0 V CR2032 lithium manganese built-in

Scope of delivery:

1 x device
 1 x user manual
 1 x power cord
 1 x frost filter
 2 x knurled screw
 1 x remote control
 1 x battery
 1 x barndoor