

EUROLITE LED CLS-6 PIX HCL

LED light effect with RGBWA/UV color mixing, incl. IR remote control

Art. No.: 51913909

GTIN: 4026397731705



List price: 236.81 €

incl. 19% VAT.

Features:

- 24 LEDs 8 W SMD 9090 6in1 RGBWA/UV (homogenous color mix)
 segments controlled separately
- Dimmer electronic; color blend; color change
- Strobe effect; wash effect
- 8 integrated show programs
- Direct color selection for 21 preset colors
- Can be operated in 5; 6; 10; 10-1; 26; 36 CH mode
- The device is cooled by cooling fan
- Control via sound to light via microphone; IR remote control; stand-alone; DMX; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional); master/slave function
- Flicker-free
- With a beam angle of 30°
- With mounting bracket
- 4 digit 7-segment LED display
- Mains input and output for power linking up to 8 units
- For application areas such as: Stage; clubs/dancing school; wedding/gala/events; mobile djs / entertainer; party room; restaurants, bars and hotels
- Application possibility: Suspended; on stand

Logistic

EAN / GTIN: 4026397731705

Weight: 3,37 kg

Length: 0.34 m

Width: 0.28 m

Height: 0.18 m

Technical specifications:

Power supply: 100-240 V AC, 50/60 Hz

Power consumption: 75 W

Protection class:	Protection class I
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug
Cable construction:	3 x 0.75 mm² H05VV-F
Power output:	IEC connector (F) mounting version
Fuse:	5 x 20 mm, T 1 A fuse replaceable
Lamp type:	LED lamp
LED type:	24 x 8 W SMD 9090 6in1 RGBWA/UV (homogenous color mix)
Flash rate:	0 - 20 Hz
DMX channels:	5; 6; 10; 10-1; 26; 36
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	2 x cooling fan
Control:	Sound to light via microphone; IR remote control; stand-alone; DMX; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional); master/slave function
Fixtures available for:	Light´J; Light Captain; Colorchief
Projection:	Flicker-free
Beam angle:	30°
Beam angle (1/2 peak):	30°
Beam angle (1/10 peak):	52°
Housing color:	Black
Attachment system:	Mounting bracket
Display type:	4 digit 7-segment LED display
USB port:	1 x type A
Material:	Metal
Dimensions:	Width: 29.1 cm Depth: 15.7 cm Height: 27.7 cm
Weight:	3.01 kg
Noise classification:	Class 2 (slight noise)
Battery:	1 x button cell 3.0 V CR2032 lithium manganese built-in

Scope of delivery:

1 x light effect
 1 x user manual
 1 x power cord
 1 x remote control
 1 x battery