

EUROLITE LED PAR-64 QCL 12x8W floor sil

PAR spot with 12 x 8 W 4in1 LED and RGBW color mixing

Art. No.: 51914031

GTIN: 4026397613841



The article is no longer in our assortment.

Description:

PAR spotlight with RGBW color mixing incl. remote control

The Eurolite LED PAR-64 is equipped with 12 powerful RGBW-LEDs (4in1) of 8 Watt each. You can use it on stage, in the club lighting area or as a floor spot, thanks to its additional bracket for placement.

The color temperature of the white tone is adjustable in six steps, the RGBW color mixing is stepless. 24 colors can be selected directly. The spotlight has a dimmer and strobe effect.

The effect spot can be controlled via DMX, standalone or via music control via the built-in microphone with adjustable microphone sensitivity. In auto and music mode you can play the integrated show programs.

Addressing and settings are possible via a control unit with four-digit LED display. Up to eight devices can be easily interconnected using the existing IEC mains connections.

The Eurolite LED PAR-64 can be easily remote controlled with the supplied infrared remote control.

Logistic

EAN / GTIN: 4026397613841

Weight: 3,00 kg

Length: 0.26 m

Width: 0.26 m

Height: 0.34 m

Features:

- 12 high-power 8 W RGBW LEDs (4in1)
- Built-in auto and music show programs
- Color temperature adjustable in 6 steps (2700-8000 K)
- Direct color selection for 24 preset colors
- Stepless RGBW color blend, color change, color fade, dimmer and strobe effect
- Addressing and setting via control panel with 4-digit LED display
- Convenient wireless control via included IR remote control EUROLITE IR-7
- Swivel mounting bracket

- Additional bracket for floor use
- Feed-through output allows to power up to 8 devices
- Switch-mode power supply for operation between 100 and 240 volts
- 12 LEDs 8 W high-power 4in1 RGBW (homogenous color mix)
- Strobe effect
- Can be operated in 2; 3; 4; 5; 6; 9 CH mode
- Control via stand-alone; DMX; IR remote control; sound to light via microphone; master/slave function
- Flicker-free
- With a beam angle of 14°

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	70 W
Protection class:	Protection class I
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Power output:	1 x IEC connector (F) mounting version
Lamp type:	LED lamp
LED type:	12 x 8 W high-power 4in1 RGBW (homogenous color mix)
DMX channels:	2; 3; 4; 5; 6; 9
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Control:	Stand-alone; DMX; IR remote control; sound to light via microphone; master/slave function
Fixtures available for:	Light J; LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE
Projection:	Flicker-free
Beam angle:	14°
Beam angle (1/2 peak):	14°
Beam angle (1/10 peak):	29°
Housing color:	Silver
Dimensions:	Width: 29.6 cm Depth: 27.3 cm Height: 34 cm
Weight:	2.60 kg
Battery:	1 x button cell 3.0 V CR2025 lithium manganese built-in

Scope of delivery:

1 x remote control